



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## CHMS Blank Dead Front Directory Marking Strip

*Eaton Corp*

Catalog Number	CHMS
Manufacturer	Eaton Corp
Description	Eaton CH 3/4-Inch Loadcenter and Breaker Accessories - Circuit Marking Strip, Circuit Marking Strip, CH, 0.75 In, Used With Type CH Style 3/4 In Loadcenter and Breakers
Weight per unit	0.1000 (lbs/each)
Product Category	Load Center Accessories

### Features

amperage rating	225
dimensions	4.0000 IN X 7.0000 IN X 0.0100 IN
interrupt rating	10
media	Yes
Phase	3

### Dimensions and Weight

Depth	4
Height	0.01
Width	7

### Descriptions

Description	BLANK DEAD FRONT DIRECTORY MARKING STRIP
extra long description	ETN CHMS Blank Dead Front Directory
Features	Eaton's CH 3/4-inch loadcenters enclose CH circuit breakers for power distribution and circuit protection in residential and light commercial applications. Also called a breaker box, electrical box or even a fuse box, the main function is to take electricity supplied by the utility and distribute it throughout the home to feed lights and receptacles. Covers are typically packaged separately and available as surface or flush mount.
Long Description	Eaton CH 3/4-inch Loadcenter and Breaker Accessories - Circuit Marking Strip,Circuit marking strip,CH,0.75 in,Used with Type CH Style 3/4 in Loadcenter and Breakers
Product Type	Blank Dead Front Directory Marking Strip
Special Features	Used with Type CH Style 3/4 in Loadcenter and Breakers

### Manufacturer Information

Brand	EATON CUTLER-HAMMER
GTIN	00782113099729
Manufacturers Part Number	CHMS
UPC	782113099729



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Type ..... Accessory .....

## Packaging

Carton ..... 1 .....

Package ..... 10 .....

Weight Per each ..... 0.1 .....

## Uses, Certifications, and Standards

Application ..... Other .....

standard ..... UL 489 .....