

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



UPC

CHP24L125R CH Pon Loadcntr 125A Mlo 24 Space N3R *Eaton Corp*

Catalog Number	CHP24L125R
Manufacturer	Eaton Corp
Description	Eaton CH Main Lug Loadcenters, Cover Included, Main Lug Only, 125A, X5, Copper, Nema 3R, Metallic, Overhead, 48, 24, Three-Wire, Single-Phase
Weight per unit	27.0 (lbs/each)
Product Category	Single Phase Main Lug Load Cen
Features	
amperage rating	125
interrupt rating	25
media	Yes
number of spaces	24
Phase	1
Dimensions and Weight	
Depth	29
Height	5.19
Size	X5
Width	14.31
Descriptions	
Description	CH PON LOADCNTR 125A MLO 24 SPACE N3R
extra long description	ETN CHP24L125R CH PON LC, 125A, MLO
Features	Eaton's CH 3/4-inch loadcenters enclose CH circuit breakers for power distribution and circuit protection in residential and light commercial applications. Also called a breaker box, electrical box or even a fuse box, the main function is to take electricity
	supplied by the utility and distribute it throughout the home to feed lights and receptacles. Covers are typically packaged separately and available as surface or flush mount.
Long Description	Eaton CH main lug loadcenters,Cover included,Main Lug Only,125A,X5,Copper,NEMA 3R,Metallic,Overhead,48,24,Three-wire,Single-phase
Product Type	CUIDONIC 12EA MIO 24CD N2D
Special Features	Cover included
Manufacturer Information	
Brand	Eaton
GTIN	00786689058616
Manufacturers Part Number	CHP24L125R

786689058616



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories	
Category Description	LOADCENTERS & COVERS
Туре	Main lug loadcenter
Packaging	
Carton	1
Weight Per each	27
Uses, Certifications, and Standards	
Application	Residential Bldgs & Facilities - Residential Bldgs & Facilities -
	Other

UL 67,UL 50