Eaton CHR7N7N5GS

Catalog Number: CHR7N7N5GS

Eaton pedestal mount metered, Pos 1: Non-gnd fault, Pos 2: Non-gnd fault, Pos 3: Gnd fault, Top, Surface, Circuits: 4, Center: NEMA 5-20R2GFI, Left: NEMA 5-20R2GFI, Right: NEMA 6-20R2, Ringless

General specifications



Eaton pedestal mount metered

UPC

782114239841

Product Height

7.8 in

Product Weight

26 lb

Catalog Number

CHR7N7N5GS

Product Length/Depth

31 in

Product Width

10 in

Warranty

Eaton Selling Policy 25-000, one (1) year

from the date of installation of the

Product or eighteen (18) months from the

date of shipment of the Product,

whichever occurs first.

Certifications

UL 231

UL Listed file E163588



Physical Attributes

Circuit breaker position 1

Non-ground fault

Circuit breaker position 2

Non-ground fault

Circuit breaker position 3

Ground fault

Feed type

Top

Mounting

Surface

Number of circuits

Receptacle center

NEMA 5-20R2GFI

Receptacle left

NEMA 5-20R2GFI

Receptacle right

NEMA 6-20R2

Type

Metered-ringless

Miscellaneous

Utility approvals

IA: Alliant (IP&L and WP&L) WI: Alliant (IP&L and WP&L)

FL: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

IN: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

KY: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

NC: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

OH: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

SC: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

FL: Tallahassee City Electric

Resources

Specifications and datasheets

Eaton Specification Sheet - CHR7N7N5GS



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.









Eaton.com/socialmedia