Eaton CHR7N7N5GS

Catalog Number: CHR7N7N5GS

Eaton pedestal mount metered, Pos 1: Non-gnd fault, Pos 2: Nongnd fault, Pos 3: Gnd fault, Top, Surface, Circuits: 4, Center: NEMA 5-20R2GFI, Left: NEMA 5-20R2GFI, Right: NEMA 6-20R2, Ringless

General specifications

Product Name Eaton pedestal mount metered

UPC 782114239841

Product Height 7.8 in

Product Weight 26 lb CHR7N7N5GS Product Length/Depth 31 in

Catalog Number

Product Width 10 in

Warranty

Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Certifications UL 231 UL Listed file E163588



Physical Attributes

Circuit breaker position 1	Utility approvals
Non-ground fault	IA : Alliant (IP&L and WP&L)
Circuit breaker position 2	WI : Alliant (IP&L and WP&L) FL : MEG (Duke Energy, Florida Power, Tampa Electric, Gulf
Non-ground fault	Power, Oklahoma Gas and Electric)
Circuit breaker position 3	IN : MEG (Duke Energy, Florida Power, Tampa Electric, Gulf
Ground fault	Power, Oklahoma Gas and Electric)
	KY : MEG (Duke Energy, Florida Power, Tampa Electric, Gulf
Feed type	Power, Oklahoma Gas and Electric)
Тор	NC : MEG (Duke Energy, Florida Power, Tampa Electric, Gulf
Mounting	Power, Oklahoma Gas and Electric)
Mounting	OH : MEG (Duke Energy, Florida Power, Tampa Electric, Gulf
Surface	Power, Oklahoma Gas and Electric)
Number of circuits	SC : MEG (Duke Energy, Florida Power, Tampa Electric, Gulf
4	Power, Oklahoma Gas and Electric)
	FL : Tallahassee City Electric
Receptacle center	
NEMA 5-20R2GFI	
Receptacle left	Resources
NEMA 5-20R2GFI	Specifications and datasheets

Miscellaneous

Eaton Specification Sheet - CHR7N7N5GS



Receptacle right

NEMA 6-20R2

Metered-ringless

Туре

Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com Reserved.

Eaton is a registered trademark.

All other trademarks are © 2025 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia