

# Specifications



Photo is representative



## Eaton CHR8N8NSU

Eaton pedestal mount metered, Pos 1: Gnd fault, Pos 2: Non-gnd fault, Pos 3: None, Bottom, Surface, Circuits: 4, Weather-resist center and left receptacle, Center: NEMA 5-20R2GFI WR, Left: NEMA 5-20R2GFI WR, Right: None, Ringless

### General specifications

|                             |  |
|-----------------------------|--|
| <b>PRODUCT NAME</b>         | Eaton pedestal mount metered   |
| <b>CATALOG NUMBER</b>       | CHR8N8NSU  |
| <b>UPC</b>                  | 786685404202   |
| <b>PRODUCT LENGTH/DEPTH</b> | 7.25 in  |
| <b>PRODUCT HEIGHT</b>       | 31 in  |
| <b>PRODUCT WIDTH</b>        | 10 in  |
| <b>PRODUCT WEIGHT</b>       | 30 lb  |
| <b>WARRANTY</b>             | Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first. |
| <b>CERTIFICATIONS</b>       | UL 231<br>UL Listed file E163588   |



Powering Business Worldwide

## Product specifications

|                                   |  |
|-----------------------------------|--|
| <b>SPECIAL FEATURES</b>           | Water resistant left/center receptacle |
| <b>TYPE</b>                       | Metered-ringless                       |
| <b>CIRCUIT BREAKER POSITION 1</b> | Ground fault                           |
| <b>CIRCUIT BREAKER POSITION 2</b> | Non-ground fault                       |
| <b>CIRCUIT BREAKER POSITION 3</b> | None                                   |
| <b>RECEPTACLE CENTER</b>          | NEMA 5-20R2GFI                         |
| <b>RECEPTACLE LEFT</b>            | NEMA 5-20R2GFI                         |
| <b>RECEPTACLE RIGHT</b>           | None                                   |
| <b>FEED TYPE</b>                  | Bottom                                 |
| <b>MOUNTING</b>                   | Surface                                |
| <b>NUMBER OF CIRCUITS</b>         | 4                                      |

## Resources

|                                      |  |
|--------------------------------------|--|
| <b>CATALOGS</b>                      | <a href="#">Residential and Light Commercial Power Pedestals, Volume 1 Tab 5</a> |
| <b>SPECIFICATIONS AND DATASHEETS</b> | <a href="#">Eaton Specification Sheet - CHR8N8NSU</a>                            |

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.



# Specifications



Photo is representative



## Eaton CHR8N8NSU

Eaton pedestal mount metered, Pos 1: Gnd fault, Pos 2: Non-gnd fault, Pos 3: None, Bottom, Surface, Circuits: 4, Weather-resist center and left receptacle, Center: NEMA 5-20R2GFI WR, Left: NEMA 5-20R2GFI WR, Right: None, Ringless

### General specifications

|                             |  |
|-----------------------------|--|
| <b>PRODUCT NAME</b>         | Eaton pedestal mount metered   |
| <b>CATALOG NUMBER</b>       | CHR8N8NSU  |
| <b>UPC</b>                  | 786685404202   |
| <b>PRODUCT LENGTH/DEPTH</b> | 7.25 in  |
| <b>PRODUCT HEIGHT</b>       | 31 in  |
| <b>PRODUCT WIDTH</b>        | 10 in  |
| <b>PRODUCT WEIGHT</b>       | 30 lb  |
| <b>WARRANTY</b>             | Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first. |
| <b>CERTIFICATIONS</b>       | UL 231<br>UL Listed file E163588   |



Powering Business Worldwide

## Product specifications

|                                   |  |
|-----------------------------------|--|
| <b>SPECIAL FEATURES</b>           | Water resistant left/center receptacle |
| <b>TYPE</b>                       | Metered-ringless                       |
| <b>CIRCUIT BREAKER POSITION 1</b> | Ground fault                           |
| <b>CIRCUIT BREAKER POSITION 2</b> | Non-ground fault                       |
| <b>CIRCUIT BREAKER POSITION 3</b> | None                                   |
| <b>RECEPTACLE CENTER</b>          | NEMA 5-20R2GFI                         |
| <b>RECEPTACLE LEFT</b>            | NEMA 5-20R2GFI                         |
| <b>RECEPTACLE RIGHT</b>           | None                                   |
| <b>FEED TYPE</b>                  | Bottom                                 |
| <b>MOUNTING</b>                   | Surface                                |
| <b>NUMBER OF CIRCUITS</b>         | 4                                      |

## Resources

|                                      |  |
|--------------------------------------|--|
| <b>CATALOGS</b>                      | <a href="#">Residential and Light Commercial Power Pedestals, Volume 1 Tab 5</a> |
| <b>SPECIFICATIONS AND DATASHEETS</b> | <a href="#">Eaton Specification Sheet - CHR8N8NSU</a>                            |

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

