

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CJ688TGBU Mini-Com Utp RJ45 Cat 6 TG Jack Module, Blue Panduit Corporation

Catalog Number	CJ688TGBU
Manufacturer	Panduit Corporation
Description	The Mini-Com [®] Cat 6 Utp RJ45 TG Jack Module Is Designed to
	Terminate 4-Pair, 22-26 Awg Twisted Pair Cable. Each Module Is
	100% Factory Tested to Exceed Industry Standard Performance
	Requirements. TG Style Termination Eliminates The Need For A
	Termination Tool. Each Jack Is Individually Serialized For
	Traceability and Is Compatible With Mini-Com Modular Patch
	Panels and Faceplates. The Jack Module Is Blue.
Weight per unit	0.0240 (lbs/each)
Product Category	Wiring Devices
Features	
Cable Entry	T568A/T568B
Material	ABS/Polycarbonate
media	Yes
Material, Color, and Finish	
Color	Blue
Dimensions and Weight	
Depth	1.5
Width	0.62
Descriptions	
Description	MINI-COM UTP RJ45 CAT 6 TG JACK MODULE, BLUE
extra long description	PAN CJ688TGBU Mini-Com [®] UTP RJ45 Ca
Long Description	The Mini-Com [®] Cat 6 UTP RJ45 TG Jack Module is designed to
	terminate 4-pair, 22-26 AWG twisted pair cable. Each module is
	100% factory tested to exceed industry standard performance
	requirements. TG style termination eliminates the need for a
	termination tool. Each jack is individually serialized for
	traceability and is compatible with Mini-Com Modular Patch
	Panels and Faceplates. The jack module is blue.
Product Type	Mini-Com [®] Utp RJ45 Cat 6 TG Jack Module, Blue
Manufacturer Information	
Brand	Panduit®
GTIN	00074983395460
Manufacturers Part Number	CJ688TGBU
Model	Mini-Com [®]
UPC	074983395460



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Туре	JACK MODULE
Packaging Carton	1
Package	50
Weight Per each	0.024
Uses, Certifications, and Standards Application	Unshielded
standard	Exceeds component and channel requirements of ANSI/TIA-568.2-D Category 6 and ISO 11801 Class E standards at swept frequencies 1 to 250 MHz for Supporting 10GBASE-T Transmission Over Twisted Pair Cabling Systems in a 4-Connector Configuration up to 100 met