ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685



CLB75MN 3/4" MALL CLAMP BACK

APPLETON/OZ GEDNEY

Catalog Number	CLB75MN
Manufacturer	APPLETON/OZ GEDNEY
Description	Appleton Clamp Back, Size: 3/4 IN, Material: Malleable Iron, Finish: Hot Dipped Galvanized, Length: 2-1/2 IN, Width: 1.13 IN, Height: 1/2 IN, Bolt Diameter: 1/4 IN, Standard: CSA C22.2 No. 18.4, CSA 065178, For Used To Support Runs Of RMC, IMC An
Weight per unit	0.1100 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

Features

Material	Malleable Iron

Material, Color, and Finish

Finish	HOT DIPPED GALVANIZED

Dimensions and Weight

Size	3/4

Descriptions

Description	3/4" MALL CLAMP BACK
Long Description	Appleton Clamp Back, Size: 3/4 IN, Material: Malleable Iron, Finish: Hot Dipped Galvanized, Length: 2-1/2 IN, Width: 1.13 IN, Height: 1/2 IN, Bolt Diameter: 1/4 IN, Standard: CSA C22.2 No. 18.4, CSA 065178, For Used To Support Runs Of RMC, IMC An
Product Type	3/4 In RDG Clampback
Special Features	provide spacing from mounting surface when used with pipe clamps
Extra Long Description	APP CLB-75MN 3/4 IN RDG CLAMPBACK

Manufacturer Information

Brand	Appleton
	Appleton Electric
GTIN	00781381875851
Manufacturers Part Number	CLB-75MN
UPC	781381

Taxonomies, Classifications, and Categories

Category Description	RIGID STRAPS & CLAMPBACKS
Type	Clamp Back

Packaging

Carton	25
Package	250
Weight Per Each	0.1100 (lbs/each)

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685

Uses, Certifications, and Standards

Application	For Used To Support Runs Of RMC, IMC And EMT
Standard	CSA 065178;CSA C22.2 No. 18.4

Beam Clamps, Straps, Clamps and Clamp Backs for Rigid Metal Conduit or IMC

Catalog Number	Trade Size (Inches)	Dimensions in Inches/Millimeters A	B	C	Hole Diameter	Weight Lbs./Kgs. Per 100	
Combination Clamp and Clamp Backs — Steel/Zinc Electroplate							
 **CL-50CB**	1/2	—	—	—	—	5.00/2.27	
CL-75CB	3/4	—	—	—	—	5.00/2.27	—
CL-100CB	1	—	—	—	—	6.00/2.72	
One-Hole Clamps — Steel/Zinc Electroplate							
CL-25	1/4	0.63/16.0	0.47/11.9	0.59/15.0	0.25/6.3	1.70/0.77	
CL-38	3/8	0.81/20.6	0.63/16.0	0.69/17.5	0.28/7.1	2.60/1.18	
CL-50	1/2	1.00/25.4	0.75/19.1	0.94/23.9	0.28/7.1	5.00/2.27	
CL-75	3/4	1.16/29.5	0.75/19.1	1.13/28.7	0.28/7.1	5.90/2.68	
 **CL-100**	1	1.34/34.0	0.88/22.4	1.44/36.6	0.34/8.6	12.20/5.53	
CL-125	1-1/4	1.69/42.9	1.00/25.4	1.78/45.2	0.41/10.4	19.00/8.62	
CL-150	1-1/2	1.94/49.3	1.13/28.7	2.00/50.8	0.41/10.4	25.00/11.34	
CL-200	2	2.34/59.4	1.19/30.2	2.53/64.3	0.47/11.9	38.00/17.24	
CL-250	2-1/2	2.81/71.4	1.25/31.8	3.03/77.0	0.56/14.2	76.00/34.47	
CL-300	3	3.31/84.1	1.25/31.8	3.66/93.0	0.56/14.2	93.00/42.18	
CL-350	3-1/2	3.44/87.4	1.50/38.1	4.16/105.7	0.69/17.5	123.00/55.79	
CL-400	4	3.78/96.0	1.50/38.1	4.66/118.4	0.69/17.5	140.00/63.50	
Clamp Backs — Steel — Can be used with EMT							
 **CLB-50**	1/2	2.06/52.3	0.88/22.4	0.25/6.4	—	5.00/2.27	
CLB-75	3/4	2.50/63.5	1.00/25.4	0.25/6.4	—	7.00/3.18	
CLB-100	1	2.69/68.3	1.13/28.7	0.25/6.4	—	8.60/3.90	

© September 2010