

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Product Type

CLT25FC20 Loom Tubing Panduit Corporation

and the same of th			
Catalog Number	CLT25FC20		
Manufacturer	Panduit Corporation		
Description	The CLT25F-C20 Corrugated Loom Slit Wall Tubing Protects Cables From Impact and Abrasion. Features A Slit For Easy Installation Onto A Bundle Of Wires or A Pre-Assembled Harness Assembly, Increasing Productivity. Hold In Place With Cable Ties and Accessories. Suitable For Indoor Applications. UL94-HB Flammability Rating and A Maximum Temperature Rating Of 122°F (50°C). Polyethylene. Inside Diameter 0.281" (7.14MM). Color Black. 1 Per Package.		
Weight per unit	2.0 (lbs/each)		
Product Category			
eatures			
Inside Diameter	0.281		
Material			
media	Yes		
outside diameter	0.4		
Material, Color, and Finish			
Color	Black		
Dimensions and Weight			
Length	100		
Descriptions			
Description	LOOM TUBING		
extra long description	PAN CLT25F-C20 Corr. Loom Tubing SI		
Long Description	The CLT25F-C20 Corrugated Loom Slit Wall Tubing protects cables from impact and abrasion. Features a slit for easy		
	installation onto a bundle of wires or a pre-assembled harness assembly, increasing productivity. Hold in place with cable ties and accessories. Suitable for indoor applications. UL94-HB flammability rating and a maximum temperature rating of 122°l (50°C). Polyethylene. Inside diameter 0.281" (7.14mm). Color Black. 1 per package.		
- · · -			

Corr. Loom Tubing Slit, .25" (6.35MM) X 100', Black, PK1



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	A	•			
n	/เวทเ	けつへけい	Iror	Intorn	うつけいへい
ı١	/Iaiiu	II a L L L	11 CI	HIIVIII	nation

Brand	PANDUIT
GTIN	00074983287109
Manufacturers Part Number	CLT25F-C20
UPC	074983287109

Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
Туре	Corrugated Loom Tubing

Packaging

Carton	10
Package	4
Weight Per each	2

Uses, Certifications, and Standards

Application	Covers wire and cable to protect from abrasion
standard	RoHS Compliant
Temperature Rating	122