



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## CSB20AC4I 20A 120/277VAC B+S Wire Comm 4W SW Iv

*Pass & Seymour/Legrand*

|                  |                                                                                                                                                                                                                                                                |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Catalog Number   | CSB20AC4I                                                                                                                                                                                                                                                      |
| Manufacturer     | Pass & Seymour/Legrand                                                                                                                                                                                                                                         |
| Description      | Toggle Switch, 4 Poles, 4 Ways, 20 A, 120/277 V Ac, Nylon Material, Silver Cadmium Oxide Contact Material, Ivory, Grounding Connection, Wall Mount, 1.320 (L) X 1.073 (W) X 3.281 (H) In, -40 °C Operating Temperature, +115 °C Operating Temperature, 0.19 LB |
| Weight per unit  | 0.1905 (lbs/each)                                                                                                                                                                                                                                              |
| Product Category | Gen Purpose Switches                                                                                                                                                                                                                                           |

### Features

|                 |                   |
|-----------------|-------------------|
| action          | Four pole         |
| amperage rating | 20                |
| Contact Rating  | 15amp, 120/277vac |
| insulation      | False             |
| Poles           | 4-Way             |
| Switch Type     | Toggle            |
| Voltage         | 120.0 V           |
| Wire Size       | #14 - #10 Awg     |

### Material, Color, and Finish

|        |       |
|--------|-------|
| Finish | Matte |
|--------|-------|

### Dimensions and Weight

|      |        |
|------|--------|
| Size | 3.3 in |
|------|--------|

### Descriptions

|                        |                                      |
|------------------------|--------------------------------------|
| Description            | 20A 120/277VAC B+S WIRE COMM 4W SW I |
| extra long description | P&S CSB20AC4I 20A 120/277VAC B+S WI  |

### Manufacturer Information

|                           |                  |
|---------------------------|------------------|
| Brand                     | Pass and Seymour |
| GTIN                      | 00785007126372   |
| Manufacturers Part Number | CSB20AC4I        |
| UPC                       | 785007126372     |

### Taxonomies, Classifications, and Categories

|                      |                        |
|----------------------|------------------------|
| Category Description | Industrial receptacles |
| Type                 | TOGGLE SWITCH          |

### Trade Size

|          |      |
|----------|------|
| Amperage | 20.0 |
|----------|------|



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

|                 |        |
|-----------------|--------|
| Carton          | 10     |
| Package         | 50     |
| Weight Per each | 0.1905 |

## Uses, Certifications, and Standards

|             |                                             |
|-------------|---------------------------------------------|
| Application | Commercial                                  |
| Enclosure   | Nylon                                       |
| Mounting    | WALL                                        |
| standard    | UL, CSA, FEDSPEC, CULUS, UL 498/20, FEDSPEC |