

## **ELLIOTT ELECTRIC SUPPLY**

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## CSL4LSCS \*Delisted\* 4' Led Strip 35K/40K/50K Lumen Select Hubbell Lighting/Current Hli

|     | Catalog Number                     | CSL4LSCS   |
|-----|------------------------------------|--|
|     | Manufacturer                       | Hubbell Lighting/Current Hli   |
|     | Description                        | CSL Led Striplight, 4 FT, Lens Type: Frosted Acrylic Lens, CCT and Lumen Switchable, 0-10V Dimming Driver, 120-277V. |
|     | Weight per unit                    | 5.2 (lbs/each)   |
|     | Product Category                   | Lighting   |
| Fea | tures                              |  |
|     | Voltage Rating                     | 120-277  |
| Mat | terial, Color, and Finish          |  |
|     | Color                              | White  |
| Des | criptions                          |  |
|     | Description                        | *DELISTED* 4' LED STRIP 35K/40K/50K LUMEN SELECT   |
|     | extra long description             | COL CSL4-LSCS STRIP 4FT LED SWITCH   |
|     | Long Description                   | CSL LED Striplight, 4 ft, Lens Type: frosted acrylic lens, CCT and   |
|     |                                    | Lumen Switchable, 0-10V dimming driver, 120-277V.  |
|     | Product Type                       | Strip 4FT Led Switch Lum Switch CCT Dim  |
| Ma  | nufacturer Information             |  |
|     | Brand                              | COLUMBIA LIGHTING  |
|     | GTIN                               | 00840141403625   |
|     | Manufacturers Part Number          | CSL4-LSCS  |
|     | UPC                                | 840141403625   |
| Тах | onomies, Classifications, and Cate | gories   |
|     | Category Description               | LED ARCHITECTURAL & SPECIFICATION LIGHTING   |
|     | Туре                               | Strips   |
| Pac | kaging                             |  |
|     | Carton                             | 1  |
|     | Weight Per each                    | 5.2  |
| Use | s, Certifications, and Standards   |  |
|     | Application                        | Manufacturing, Warehouse, Offices, Hospitality, Retail,  |
|     |                                    | Automotive Dealers, Educational  |
|     | Mounting                           | Ceiling, Surface, Wall   |
|     | standard                           | UL, UL 1598, UL1598 Damp Location  |