

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



UPC

CTAPF412C Comp C-Tap *Panduit Corporation*

Catalog Number	CTAPF412C
Manufacturer	Panduit Corporation
Description	The CTAPF4-12-C Compression Connector Tap Provides
	High-Strength and Premium Electrical Properties. It Is Suitable
	For Use With Stranded Copper Code Conductors and Is For Tapping Into Unbroken Continuous Main, Splicing and Pig Tailing.
	The Wide Wire Range-Taking Capability Minimizes Inventory
	Requirements. UI Listed Per UL486 For Use Up to 600V and
	Temperature Rated to 90°C When Crimped With Panduit and
	Specified Competitor Crimping Tools and Dies.
Weight per unit	
Product Category	Large Terminals & Connectors
Features	
Material	Copper
Number of Holes	0
Material, Color, and Finish	
Clamp Material	Copper
Color	Brown
Dimensions and Weight	
Length	1.25
Descriptions	
Description	COMP C-TAP
extra long description	PAN CTAPF4-12-C StructuredGround™ C
Long Description	The CTAPF4-12-C Compression Connector Tap provides
	high-strength and premium electrical properties. It is suitable for
	use with stranded copper code conductors and is for tapping into
	unbroken continuous main, splicing and pig tailing. The wide wire range-taking capability minimizes inventory requirements. UL
	listed per UL486 for use up to 600V and temperature rated to
	90°C when crimped with Panduit and specified competitor
	crimping tools and dies.
Product Type	Structuredground™ CTAPF4-12-C Comp. Tap, Copper, Copper, PK1
Manufacturer Information	
Brand	PANDUIT
GTIN	00074983599738
Manufacturers Part Number	CTAPF4-12-C

074983599738



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories	
Category Description	Comp & Mech Lugs and Butt Splices
Туре	Compression Tap
Packaging	
Carton	100
Weight Per each	0.027
Uses, Certifications, and Standards	
standard	UL listed and CSA certified to 600 V