

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CTAPF412C Comp C-Tap Panduit Corporation

Catalog Number	CTAPF412C
Manufacturer	Panduit Corporation
Description	The CTAPF4-12-C Compression Connector Tap Provides High-Strength and Premium Electrical Properties. It Is Suitable For Use With Stranded Copper Code Conductors and Is For Tapping Into Unbroken Continuous Main, Splicing and Pig Tailing. The Wide Wire Range-Taking Capability Minimizes Inventory
	Requirements. UI Listed Per UL486 For Use Up to 600V and Temperature Rated to 90°C When Crimped With Panduit and Specified Competitor Crimping Tools and Dies.
Weight per unit	
Product Category	
Features	
Material	Copper
Number of Holes	0
Material, Color, and Finish Clamp Material	Copper
Color	Brown
Dimensions and Weight	
Length	1.25
Descriptions	
Description	COMP C-TAP
extra long description	PAN CTAPF4-12-C StructuredGround™ C
Long Description	The CTAPF4-12-C Compression Connector Tap provides
	high-strength and premium electrical properties. It is suitable for use with stranded copper code conductors and is for tapping into unbroken continuous main, splicing and pig tailing. The wide wire range-taking capability minimizes inventory requirements. UL listed per UL486 for use up to 600V and temperature rated to 90°C when crimped with Panduit and specified competitor crimping tools and dies.
Product Type	Structuredground™ CTAPF4-12-C Comp. Tap, Copper, Copper, PK1



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	PANDUIT
GTIN	00074983599738
Manufacturers Part Number	CTAPF4-12-C
UPC	074983599738
Taxonomies, Classifications, and C	ategories
Category Description	Comp & Mech Lugs and Butt Splices
Туре	Compression Tap
Packaging	
Carton	100
Weight Per each	0.027
Uses, Certifications, and Standard	
standard	UL listed and CSA certified to 600 V