

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CTH111 4/0-1 Main Copper C Tap *Nsi Industries*

Nsi Industries	
Catalog Number	CTH111
Manufacturer	Nsi Industries
Description	Heavy Duty Copper C Tap Grounding Connector For 4/0 to 1 Awg Applications: Copper "C" Taps Ensure Positive, All Around Compression With Low-Resistance and High Pull-Out Values. Made Of High Conductivity Copper, They Satisfy The Requirements Of NEC250-81 and 250-91 For Connecting to The Grounding Electrode System. Rated 600 Volts.
Weight per unit	0.1000 (lbs/each)
Product Category	
Features	
Conductor Size	4/0 AWG
Material	
Tap Size	8 AWG
Voltage Rating	600 V
Warranty	1 YEAR
Material, Color, and Finish	
Color	Blue
Finish	CODDED
Dimensions and Weight	
Size	4/0-8 AWG
Descriptions	
Description	4/0-1 MAIN COPPER C TAP
extra long description	
Features	Heavy Duty Copper C Tap Grounding Connector for 4/0 to 1 AWG APPLICATIONS: Copper "C" Taps ensure positive, all around compression with low-resistance and high pull-out values. Made of high conductivity copper, they satisfy the requirements of NEC250-81 and 250-91 for connecting to the grounding electrode system. Rated 600 Volts.
Long Description	Heavy Duty Copper C Tap Grounding Connector for 4/0 to 1 AWG APPLICATIONS: Copper "C" Taps ensure positive, all around compression with low-resistance and high pull-out values. Made of high conductivity copper, they satisfy the requirements of NEC250-81 and 250-91 for connecting to the grounding electrode system. Rated 600 Volts.
Product Type	Copper C Tap 4/0-1 Main
Special Features	4/0-8 AWG



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	NSi
GTIN	00662381098108
Manufacturers Part Number	CTH-111
UPC	662381098108

Taxonomies, Classifications, and Categories

Category Description	T&B C TAP LUGS
Туре	C-Taps

Packaging

maging .		
Carton	1	
Package	25	
	0.1	

Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
standard	UL486A
Temperature Rating	90 C