



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## CTP22 GRD Comp C-Tap Conn

*Abb Installation Products, Inc*

|                  |   |
|------------------|---|
| Catalog Number   | CTP22   |
| Manufacturer     | Abb Installation Products, Inc  |
| Description      | E-Z-Ground C-Taps Copper Compression Connector For Cable Range #6 Sol. - #2 STR., Tap #6 Sol. - #2 STR. |
| Weight per unit  | 0.0780 (lbs/each)   |
| Product Category | Grounding & Bonding Equipment   |

### Features

|                |             |
|----------------|-------------|
| Conductor Size | #6 - #2 AWG |
| Material       | Copper      |

### Descriptions

|                        |  |
|------------------------|--|
| Description            | GRD COMP C-TAP CONN  |
| extra long description | ABB CTP22 C-TAP, No6-2 MAIN AND TAP  |
| Long Description       | E-Z-Ground C-Taps Copper Compression Connector for Cable Range #6 Sol. - #2 Str., Tap #6 Sol. - #2 Str.                                  |
| Product Type           | C-Tap, NO6-2 Main and Tap  |
| Special Features       | E-Z-Ground <sup>®</sup> connectors are designed for direct burial and offer a safe, efficient alternative to exothermic welding products |

### Manufacturer Information

|                           |                |
|---------------------------|----------------|
| Brand                     | COLOR-KEYED    |
| GTIN                      | 00786210330969 |
| Manufacturers Part Number | CTP22          |
| UPC                       | 786210330969   |

### Taxonomies, Classifications, and Categories

|                      |                                  |
|----------------------|----------------------------------|
| Category Description | T&B C TAP LUGS                   |
| Type                 | E-Z-Ground Compression Grounding |

### Packaging

|                 |       |
|-----------------|-------|
| Carton          | 1     |
| Package         | 25    |
| Weight Per each | 0.078 |

### Uses, Certifications, and Standards

|          |          |
|----------|----------|
| standard | UL E3060 |
|----------|----------|