

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Type

DR10250L Disconnect *Panduit Corporation*

DR10250L
Panduit Corporation
The Vibration Resistant Female Disconnect Is Made Of Brass and Is Tin-Plated. It Is Non-Insulated In Metallic Housing. It Has A Tab Size Of 0.250 X 0.032" (6.3 X 0.8 MM) and Supports A Wire Range Of 12-10 Awg (4.0-6.0 MM²). It Is 0.61" (15.5 MM) Long and 0.3" (7.6 MM) Wide. The Disconnect Has A Standard Barrel Configuration and A Sleeved Barrel. It Comes In Bottles Of 50.
1.0 (lbs/each)
Small Terminals & Connectors
Standard
None
Brass
600
10
Tinned
DISCONNECT
PAN DR10-250-L Pan-Term® DR10-250-L
The vibration resistant female disconnect is made of brass and is tin-plated. It is non-insulated in metallic housing. It has a tab size of 0.250 x 0.032" (6.3 x 0.8 mm) and supports a wire range of 12-10 AWG (4.0-6.0 mm²). It is 0.61" (15.5 mm) long and 0.3" (7.6 mm) wide. The disconnect has a standard barrel configuration and a sleeved barrel. It comes in bottles of 50.
Pan-Term® DR10-250-L Loose Piece Disconnect
PANDUIT
00074983827367
DR10-250-L
074983827367
ntegories

Disconnect



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	50
Weight Per each	1
Uses, Certifications, and Standards	
Mounting	1932-09-01
standard	CSA Certified LR31212, C22.2 No.153; UL 310 Listed, UL Listed
	20H3 E78522
Temperature Rating	302 Degrees Fahrenheit (150 Degrees Celsius)