



Powering Business Worldwide

pe.eaton.com

1 in NEMA 3R Plate Type Hub

DS100H1

UPC:782113109923

Dimensions:

- **Height:** 1.25 IN
- **Length:** 2.75 IN
- **Width:** 3 IN

Weight: .2 LB

Notes: Group 1, conduit size: 3/4 inch (19.1 mm), used with 70, 100, and 125A mlo and mcb br and ch loadcenters and cb enclosures, and the following 150 and 200A panels: ch8b150rf, ch8b200rf

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Special Features:** Suitable for MLO and MCB loadcenters and CB enclosures
- **Type:** Rainproof conduit/plate type hub -group 1
- **Amperage Rating:** Up to 100A
- **Enclosure:** NEMA 3R
- **Size:** 1 in
- **Used With:** Mlo and mcb loadcenters and cb enclosures, ch8b150rf, ch8b200rf, general duty, heavy duty, and double throw safety switches through 100A. for use with rgdn and rfdn

Supporting documents:

- [Eatons Volume 1-Residential and Light Commercial](#)
- [Eaton Specification Sheet - DS100H1](#)

Certifications: No Data



Product compliance: No Data

© 2016 Eaton. All rights reserved.



Powering Business Worldwide

pe.eaton.com

1 in NEMA 3R Plate Type Hub

DS100H1

UPC:782113109923

Dimensions:

- **Height:** 1.25 IN
- **Length:** 2.75 IN
- **Width:** 3 IN

Weight: .2 LB

Notes: Group 1, conduit size: 3/4 inch (19.1 mm), used with 70, 100, and 125A mlo and mcb br and ch loadcenters and cb enclosures, and the following 150 and 200A panels: ch8b150rf, ch8b200rf

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Special Features:** Suitable for MLO and MCB loadcenters and CB enclosures
- **Type:** Rainproof conduit/plate type hub -group 1
- **Amperage Rating:** Up to 100A
- **Enclosure:** NEMA 3R
- **Size:** 1 in
- **Used With:** Mlo and mcb loadcenters and cb enclosures, ch8b150rf, ch8b200rf, general duty, heavy duty, and double throw safety switches through 100A. for use with rgdn and rfdn

Supporting documents:

- [Eatons Volume 1-Residential and Light Commercial](#)
- [Eaton Specification Sheet - DS100H1](#)

Certifications: No Data



Product compliance: No Data

© 2016 Eaton. All rights reserved.