



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



DS900AP Conduit Hub Adaptor Kit 150A 200A 225A Mains

Eaton Corp

Catalog Number	DS900AP
Manufacturer	Eaton Corp
Description	Eaton CH Loadcenter and Breaker Accessories - Conduit Hub Adapter Kit, Conduit Hub Adapter Kit, CH, Standard T, Used With Type CH Style 3/4 In Loadcenter and Breakers
Weight per unit	0.4000 (lbs/each)
Product Category	Safety Switch Accessories

Features

dimensions	8.0000 IN X 5.0000 IN X 0.2000 IN
media	Yes

Dimensions and Weight

Depth	8
Height	0.2
Width	5

Descriptions

Description	CONDUIT HUB ADAPTOR KIT 150A 200A 225A MAINS
extra long description	ETN DS900AP Condt Hub Adapt Kt 150A
Features	Eaton's CH 3/4-inch loadcenters enclose CH circuit breakers for power distribution and circuit protection in residential and light commercial applications. Also called a breaker box, electrical box or even a fuse box, the main function is to take electricity supplied by the utility and distribute it throughout the home to feed lights and receptacles. Covers are typically packaged separately and available as surface or flush mount.
Long Description	Eaton CH Loadcenter and Breaker Accessories - Conduit Hub Adapter Kit,Conduit hub adapter kit,CH,Standard T,Used with Type CH Style 3/4 in Loadcenter and Breakers
Product Type	Condt Hub Adapt KT 150A, 200A, 225A Main
Special Features	Used with Type CH Style 3/4 in Loadcenter and Breakers

Manufacturer Information

Brand	EATON CUTLER-HAMMER
GTIN	00782113099422
Manufacturers Part Number	DS900AP
UPC	782113099422

Taxonomies, Classifications, and Categories

Category Description	LOADCENTER ACCESSORIES
Type	Accessory



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	1
Weight Per each	0.4

Uses, Certifications, and Standards

Application	Other
standard	UL 489