

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



DS96 5-15R Cast Cover W/RCPT Crouse-Hinds

Catalog Number	DS96
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series DS Receptacle Housing, Feraloy Iron Alloy, Two-Wire, Three-Pole, 15A, 125 Vac, For Plugs With U Shaped or Round Grounding Contacts
Weight per unit	1.2 (lbs/each)
Product Category	FS & FD Type Boxes & Covers
eatures	
dimensions	2.8000 IN X 1.8100 IN X 4.3200 IN
Material	Feraloy Iron Alloy Housing, Copper Free Aluminum Cap
escriptions	
Description	5-15R CAST COVER W/RCPT
extra long description	CRS-H DS96 15A 125V 2W 3P CST IRON
Features	Crouse-Hinds series FS and FD device boxes are installed in non-hazardous area conduit systems to accommodate wiring devices, act as pull boxes or provide openings for taps and splices. They are suitable for use in wet locations when used with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, hul configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable iron boxes are also a
Long Description	Eaton Crouse-Hinds series DS receptacle housing, Feraloy iron alloy, Two-wire, three-pole, 15A, 125 Vac, For plugs with U shaped or round grounding contacts
Product Type	15A 125V 2W 3P CST Iron RCPT Hous
Special Features	With Cover
Nanufacturer Information	
Brand	Eaton
GTIN	00782274227009
Manufacturers Part Number	DS96
UPC	782274227009
axonomies, Classifications, and (Categories
Category Description	FS BOXES AND COVERS
Туре	Receptacle housing



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton	1
Package	2
Weight Per each	1.18

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 498, CSA C22.2