



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## DSD926 2CKT 3POS Sel-SW

*Crouse-Hinds*

Catalog Number	DSD926
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series DSD Selector Switch Cover and Device Sub-Assembly, 10A, Feraloy Iron Alloy, 3 Position, 4 Circuit, Factory Sealed, Maintained Contact, 600 Vac
Weight per unit	3.6 (lbs/each)
Product Category	Selector Switch Components

### Features

action	Maintained
amperage rating	10A
dimensions	5.2000 IN X 6.7000 IN X 4.7000 IN
Material	FERALOY IRON ALLOY
Voltage Rating	600 VAC

### Descriptions

Description	2CKT 3POS SEL-SW
extra long description	CRS-H DSD926 DSD COVER DEVICE SUB A
Features	New DSDX series available with NEMA 4X protection for Class I, Division 2 hazardous areas. Crouse-Hinds series DSD and DSDX explosionproof cover and device sub-assemblies are for use with our EDS/EDSC back boxes and EDSCM modular multi-gang device bodies. DSD/DSDX covers are available with a wide variety of devices and configurations, including manual motor starters, front operated pushbuttons, general use snap switches, side operated pushbuttons, selector switches and pilot lights. Certified for use in CI
Long Description	Eaton Crouse-Hinds series DSD selector switch cover and device sub-assembly, 10A, Feraloy iron alloy, 3 position, 4 circuit, Factory sealed, Maintained contact, 600 Vac
Product Type	DSD Cover Device Sub Assembly
Special Features	Factory sealed

### Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274776484
Manufacturers Part Number	DSD926
UPC	782274776484

### Taxonomies, Classifications, and Categories

Category Description	STANDARD DUTY PUSHBUTTONS (10250H-)
Type	Selector switch cover and device sub-assembly



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

Carton	1
Weight Per each	3.6

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Power Distribution and Control
Enclosure	Class I Div 1 2 Group B C D, Class II Div 1 Group E F G, Class II Div 2 Group F G, Class III, NEMA 3/7B/7C/7D/9E/9F/9G
standard	UL 1203, CSA C22.2