

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## **E22JL2N8 PSHPLL Ma JMSHD AI RD CRBZ Estop** *Eaton Corp*

Catalog Number	E22JL2N8
Manufacturer	Eaton Corp
Description	Eaton E22 Pushbutton, E22 Pushbutton, 22.5 MM, Non-Metallic Heavy-Duty, 50 MM, Nema 3, 3R, 4, 4X, 12, 13, Non-Illuminated, Maintained, Two-Position Push-Pull, Red Actuator, Mushroom, Anodized Aluminum, Emerg. Stop, No Light Unit
Weight per unit	
Product Category	Push Button Components
Features	·
actuator	Mushroom
<b>Dimensions and Weight</b>	
Height	1.5
Length	2
Size	50 mm
Width	1.5
Descriptions	
- Description	PSHPLL MA JMSHD AL RD CRBZ ESTOP
extra long description	ETN E22JL2N8 PSHPLL MA JMSHD AL RD
Features	Eaton's 22.5 mm industrial heavy-duty pushbutton line offers a wide array of functional, smartly styled illuminated and non-illuminated pushbuttons, selector switches, push-pulls, action and twist-to- release operators. The complete line also includes transformer, full voltage, resistor, LED or neon light units.
Long Description	Eaton E22 pushbutton, E22 Pushbutton, 22.5 mm, Non-Metallic Heavy-Duty, 50 mm, NEMA 3, 3R, 4, 4X, 12, 13, Non-illuminated, Maintained, two-position push-pull, Red actuator, Mushroom, Anodized aluminum, EMERG. STOP, No light unit
Product Type	PSHPLL Ma JMSHD AI RD CRBZ Estop
Manufacturer Information	
Brand	Eaton
GTIN	00782113504056
Manufacturers Part Number	E22JL2N8
UPC	782113504056

## **Taxonomies, Classifications, and Categories**

Category Description	MINATURE PILOT DEVICES.22MM
Type	PUSHBUTTON



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	0.08
Uses, Certifications, and Standards	
Application	Stationary Machinery and Equipment Outside Factory -
	Stationary Machinery and Equipment Outside Factory - Other
standard	IEC 947-5-1 MTTA,Lloyd's Register Certified,CSA
	Certified, UL 508, CE Marked