



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



E22LED120RD 120V Ac/DC Red Led

Eaton Corp

Catalog Number	E22LED120RD
Manufacturer	Eaton Corp
Description	Pilot Devices - Ashville Pushbutton, Led Lamp, Red, Red, Red, Continuous, 120 Vac/VDC, 22.5 MM, Led Lamp, E22, 10250T, E34 and E22 Units
Weight per unit	0.0010 (lbs/each)
Product Category	Push Button Components

Features

dimensions	0.1000 IN X 0.1000 IN X 0.1000 IN
------------	-----------------------------------

Dimensions and Weight

Size	22.5 mm
------	---------

Descriptions

Description	120V AC/DC RED LED
extra long description	ETN E22LED120RN 120V AC/DC RED LED
Features	Eaton's 22.5 mm industrial heavy-duty pushbutton line offers a wide array of functional, smartly styled illuminated and non-illuminated pushbuttons, selector switches, push-pulls, action and twist-to- release operators. The complete line also includes transformer, full voltage, resistor, LED or neon light units.
Long Description	Pilot Devices - Ashville Pushbutton, LED Lamp, Red, Red, Red, Continuous, 120 Vac/Vdc, 22.5 mm, LED lamp, E22, 10250T, E34 and E22 units
Product Type	120V Ac/DC Red Led
Special Features	LED

Manufacturer Information

Brand	Eaton
GTIN	00782113494050
Manufacturers Part Number	E22LED120RN
UPC	782113494050

Taxonomies, Classifications, and Categories

Category Description	MINATURE PILOT DEVICES.22MM
Type	Pushbutton accessory

Availability

Status	Inactive
--------	----------



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	1
Weight Per each	0.001

Uses, Certifications, and Standards

Application	Elec Assemblies, Panels & OEM - Electrical Assemblies and OEMs - Other Stationary Machinery and Equipment Outside Factory - Stationary Machinery and Equipment Outside Factory - Other
standard	CSA Std. C22.2, Lloyd's Register Certified, BS 4794, IEC 337-1, UL 508, IEC 947-5-1 MTTA, CE Marked