

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



EABC36 1" 2HUB Cond Body & CVR Crouse-Hinds

Catalog Number	EABC36
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Eab Conduit Outlet Box With Cover, 3" Cover Opening Diameter, Feraloy Iron Alloy, C Shape, 1"
Weight per unit	3.8 (lbs/each)
Product Category	Bodies & Covers
Features	
Cable Entry	(2) Side
dimensions	5.5600 IN X 2.7800 IN X 3.7500 IN
Material	FERALOY IRON ALLOY
Dimensions and Weight	
Size	1 in
-1	
Descriptions Description	1" 2HUB COND BODY & CVR
extra long description	CRS-H EABC36 1 IRON CNDT OUTLET BX
Features	Crouse-Hinds series EAB and EAJ explosionproof conduit outlet
	boxes are installed in conduit systems in hazardous areas to protect conductors in threaded rigid conduit, act as pull and splice boxes, change conduit direction, and provide access to conductors for maintenance and future system changes.EAB and EAJ outlet boxes are manufactured in five different hub configurations with mounting feet and 16 pitch cover threads.
Long Description	Eaton Crouse-Hinds series Condulet EAB conduit outlet box with cover, 3" cover opening diameter, Feraloy iron alloy, C shape, 1"
Product Type	1 Iron CNDT Outlet BX CVR
Special Features	With Cover
Manufacturer Information	
Brand	Eaton
GTIN	00782274247908
Manufacturers Part Number	EABC36
UPC	782274247908
Taxonomies, Classifications, and C	Categories
	HUB STYLE BOXES (GUAB, GUAT, ETC)
8 3 1	Conduit outlet box with cover



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton	1
Weight Per each	3.7599
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 886, CSA C22.2
Application standard	Ind Facilities & Factories - Industrial Facilities/Factories - Other UL 886, CSA C22.2