Condulet® EAB Series Conduit Outlet Boxes with Covers

Cl. I, Div. 1 & 2, Groups A, B, C, D Cl. II, Div. 1, Groups E, F, G Cl. II, Div. 2, Groups F, G Cl. III NEMA 3, 4, 7ABCD, 9EFG Explosionproof
Dust-ignitionproof
Raintight
Wet Locations

Applications:

EAB Series Conduit Outlet Boxes are installed in conduit systems within hazardous areas to:

- Provide protection against exterior explosion where acetylene, hydrogen and other hazardous gases are present
- Protect conductors in threaded rigid conduit
- Act as pull and splice boxes
- Interconnect lengths of conduit
- · Change conduit direction
- Provide access to conductors for maintenance and future system changes

Features:

EAB Series Conduit Outlet Boxes have:

- Five different hub configurations
- Taper threaded hubs to provide ground continuity
- Smooth integral hub bushing to protect conductor insulation when pulling
- Threaded cover openings
- Surface covers furnished with boxes
- Neoprene o-ring gasket and green ground screw are both standard
- Four standard mounting pads, except for EABY
- · Cover threads are 16 pitch
- Internal green ground screw #10

Certifications and Compliances:

NEC/CEC:

- Class I, Divisions 1 & 2, Groups A, B, C, D
- Class II, Division 1, Groups E, F, G
- Class II, Division 2, Groups F, G
- Class III

UL Standard:

UL1203

CSA Standard:

• C22.2 No. 30

Standard Materials:

- Bodies Feraloy® iron alloy
- Covers Copper-free aluminum

Standard Finishes:

- Feraloy electrogalvanized and aluminum acrylic paint
- Aluminum natural

Size Ranges:

- Hub ½" to 1"
- Cover opening 3" diameter

Available in copper-free aluminum. To order, add suffix 'SA' to end of catalog number.

BEAB0687 is listed for Groups C and D only.

Options:

Description	Suffix
• Bodies – copper-free aluminum	SA
Covers – Feraloy iron alloy	. WOD
Electrogalvanized and aluminum acrylic prinish	paint
 Corro-free[™] epoxy powder coat 	S752

Ordering Information: EABC



Hub Size	Cat. #
1/2"	EABC16
3/4"	EABC26
1"	EABC36

EABT



Hub Size	Cat. #
1/2"	EABT16 ©
3/4"	EABT26
1"	EABT36

EABL



Hub Size	Cat. #
1/2"	EABL16@
3/4"	EABL26
1"	EABL36

EABX



Cat. #
EABX16@
EABX26
EABX36©

EABY



Hub Size	Cat. #
1/2"	EABY16
3/4"	EABY26

Replacement Cover

Size	Cat. #
3"	EAB06

Replacement O-ring Gasket


Description	Cat. #
Replacement O-ring	GASK1151

Fixture Cover Union Hub Type



Cover Opening Dia.	Fixt. Stem Size	Cat. #
3"	3/4	EAB0687 ©

Dimensions (in Inches):



Cat. #	а	b	С	d	е	f
16	33/4	217/32	11/2	3/4	55/16	33/32
26	33/4	225/32	13/4	7/8	5 ⁹ / ₁₆	$3^3/_{32}$
36	33/4	$2^{25}/_{32}$	13/4	7/8	59/16	$3^3/_{32}$

Factory Installed Terminal Block Ordering Guide

Ordering Information:

DIN Rail Mounted Terminal Blocks

Electrical Specifications: 30 Amp, 150V, AWG 26-10

Cat. #	Description
DIN12	DIN Rail Mounted, 2 Terminal Blocks EAB (Shapes C, X, T, L) Form 6 Cover Dia. Opening
DIN13	DIN Rail Mounted, 3 Terminal Blocks EAB (Shapes C, X, T, L) Form 6 Cover Dia. Opening
DIN14	DIN Rail Mounted, 4 Terminal Blocks EAB (Shapes C, X, T, L) Form 6 Cover Dia. Opening



Direct Mounted Terminal Blocks

Electrical Specifications: 30 Amp, 300V, AWG 26-10

Cat. #	Description
TB14	Direct Mounted Terminal Block, 4 Terminal Blocks EAB (Shapes C, X, T, L) Form 6 Cover Dia. Opening
TB16	Direct Mounted Terminal Block, 6 Terminal Blocks EAB (Shapes C, X, T, L) Form 6 Cover Dia. Opening



Condulet® EAB Series Conduit Outlet Boxes with Covers

Cl. I, Div. 1 & 2, Groups A, B, C, D Cl. II, Div. 1, Groups E, F, G Cl. II, Div. 2, Groups F, G Cl. III NEMA 3, 4, 7ABCD, 9EFG Explosionproof
Dust-ignitionproof
Raintight
Wet Locations

Applications:

EAB Series Conduit Outlet Boxes are installed in conduit systems within hazardous areas to:

- Provide protection against exterior explosion where acetylene, hydrogen and other hazardous gases are present
- Protect conductors in threaded rigid conduit
- Act as pull and splice boxes
- Interconnect lengths of conduit
- · Change conduit direction
- Provide access to conductors for maintenance and future system changes

Features:

EAB Series Conduit Outlet Boxes have:

- Five different hub configurations
- Taper threaded hubs to provide ground continuity
- Smooth integral hub bushing to protect conductor insulation when pulling
- Threaded cover openings
- Surface covers furnished with boxes
- Neoprene o-ring gasket and green ground screw are both standard
- Four standard mounting pads, except for EABY
- · Cover threads are 16 pitch
- Internal green ground screw #10

Certifications and Compliances:

NEC/CEC:

- Class I, Divisions 1 & 2, Groups A, B, C, D
- Class II, Division 1, Groups E, F, G
- Class II, Division 2, Groups F, G
- Class III

UL Standard:

UL1203

CSA Standard:

• C22.2 No. 30

Standard Materials:

- Bodies Feraloy® iron alloy
- Covers Copper-free aluminum

Standard Finishes:

- Feraloy electrogalvanized and aluminum acrylic paint
- Aluminum natural

Size Ranges:

- Hub ½" to 1"
- Cover opening 3" diameter

Available in copper-free aluminum. To order, add suffix 'SA' to end of catalog number.

BEAB0687 is listed for Groups C and D only.

Options:

Description	Suffix
• Bodies – copper-free aluminum	SA
Covers – Feraloy iron alloy	. WOD
Electrogalvanized and aluminum acrylic prinish	paint
 Corro-free[™] epoxy powder coat 	S752

Ordering Information: EABC



Hub Size	Cat. #
1/2"	EABC16
3/4"	EABC26
1"	EABC36

EABT



Hub Size	Cat. #
1/2"	EABT16 ©
3/4"	EABT26
1"	EABT36

EABL



Hub Size	Cat. #
1/2"	EABL16@
3/4"	EABL26
1"	EABL36

EABX



Cat. #
EABX16@
EABX26
EABX36©

EABY



Hub Size	Cat. #
1/2"	EABY16
3/4"	EABY26

Replacement Cover

Size	Cat. #
3"	EAB06

Replacement O-ring Gasket


Description	Cat. #
Replacement O-ring	GASK1151

Fixture Cover Union Hub Type



Cover Opening Dia.	Fixt. Stem Size	Cat. #
3"	3/4	EAB0687 ©

Dimensions (in Inches):



Cat. #	а	b	С	d	е	f
16	33/4	217/32	11/2	3/4	55/16	33/32
26	33/4	225/32	13/4	7/8	5 ⁹ / ₁₆	$3^3/_{32}$
36	33/4	$2^{25}/_{32}$	13/4	7/8	59/16	$3^3/_{32}$

Factory Installed Terminal Block Ordering Guide

Ordering Information:

DIN Rail Mounted Terminal Blocks

Electrical Specifications: 30 Amp, 150V, AWG 26-10

Cat. #	Description
DIN12	DIN Rail Mounted, 2 Terminal Blocks EAB (Shapes C, X, T, L) Form 6 Cover Dia. Opening
DIN13	DIN Rail Mounted, 3 Terminal Blocks EAB (Shapes C, X, T, L) Form 6 Cover Dia. Opening
DIN14	DIN Rail Mounted, 4 Terminal Blocks EAB (Shapes C, X, T, L) Form 6 Cover Dia. Opening



Direct Mounted Terminal Blocks

Electrical Specifications: 30 Amp, 300V, AWG 26-10

Cat. #	Description
TB14	Direct Mounted Terminal Block, 4 Terminal Blocks EAB (Shapes C, X, T, L) Form 6 Cover Dia. Opening
TB16	Direct Mounted Terminal Block, 6 Terminal Blocks EAB (Shapes C, X, T, L) Form 6 Cover Dia. Opening

