


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





ECSR100 100A RK5 Time Delay Bullet Fuse Bussmann Fuses

1	
Catalog Number	ECSR100
Manufacturer	Bussmann Fuses
Description	Eaton Edison Ecsr Fuse, Time-Delay Current-Limiting Fuse, Superior Overload and Cycling Capabilities, 100 A, Dual, Class RK5, Non-Indicating, Blade End X Blade End, 10 Sec At 500%, 200 Kaic, Standard, 600 V
Weight per unit	0.3800 (lbs/each)
Product Category	Dual Element
Features	
amperage rating	100
class	Class RK5
connection	Blade End X Blade End
dimensions	9.6300 IN X 1.6100 IN X 1.6100 IN
element	Dual
Fuse Class	Class RK5

Fuse Class 200 kAIC interrupt rating

media Yes

10 S at 500% Response Time type of indicators Non-Indicating

Voltage Rating 600 V

Dimensions and Weight

Height	1.61
Length	9.63
Size	1.11 In Diameter X 7.88 In Length
Width	1,61

Descriptions

Description	100A RK5 TIME DELAY BULLET FUSE
extra long description	BUSS ECSR100 UL CLASS RK-5 TIME DEL
Features	Edison's UL Class RK5 dual-element, time-delay fuses provide
	economical solutions to overcurrent protectioni. Available in
	both 250Vac and 600Vac, with 200kA RMS Sym interrupting
	ratings and sizes ranging from 0 to 600 amp.
Long Description	EATON EDISON ECSR FUSE, TIME-DELAY CURRENT-LIMITING
	FUSE, SUPERIOR OVERLOAD AND CYCLING CAPABILITIES, 100 A,
	DUAL, CLASS RK5, NON-INDICATING, BLADE END X BLADE END,
	10 SEC AT 500%, 200 KAIC, STANDARD, 600 V
Product Type	UI Class RK-5 Time Delay
Special Features	Super lag, time lag, non current-limiting



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

$N/I \cap M \cap I$	CASTILLA	Information
11/1/41 11 11	141 III PI	
IVIGITAL	Ideldiei	

Brand	Eaton	
GTIN	00782634508434	
Manufacturers Part Number	ECSR100	
UPC	782634508434	

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSF

Packaging

onagg	
Carton	5
Weight Per each	0.38

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked