

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

15	4
	-
100	
1	2

## EDS218 2-Pos Selector Switch On/Off Crouse-Hinds

Catalog Number	EDS218
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eds Snap Switch Control Station, 20A, With Switch, With One 3/4" Hub, Feraloy Iron Alloy, 1, Single-Gang, Two-Pole, 120-277V, Factory Sealed, Dead End, Two-Pole, 3/4", 120-277 Vac
Weight per unit	
Product Category	
Features	
amperage rating	20A
dimensions	
Material	FERALOY IRON ALLOY
Poles	Two-pole
Voltage Rating	120-277 VAC
Dimensions and Weight	
Size	5-7/8 In Length X 3-1/2 In Width X 2-11/16 In Height
Descriptions	
Description	2-POS SELECTOR SWITCH ON/OFF
extra long description	CRS-H EDS218 EDS FS GENERAL USE SNA
Features	New EDSX series available with NEMA 4X protection for Class I, Division 2 hazardous areas.EDS/EDSX and EFD snap switches are used with magnetic starters or contactors for control of motors. Snap switch control stations are factory sealed to prevent arcing of the enclosed device from causing ignition of a hazardous atmosphere external to the enclosure. Factory sealing eliminates the need for external seals, simplifying installation and reducing material and labor costs.
Long Description	Eaton Crouse-Hinds series EDS snap switch control station, 20A, With switch, With one 3/4" hub, Feraloy iron alloy, 1, Single-gang, Two-pole, 120-277V, Factory sealed, Dead end, Two-pole, 3/4", 120-277 Vac
Product Type	•
Special Features	Factory sealed



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Manufacturer Information**

Brand	Eaton
GTIN	00782274763545
Manufacturers Part Number	EDS218
UPC	782274763545
Taxonomies, Classifications, and Ca	tegories
Category Description	STANDARD DUTY PUSHBUTTONS (10250H-)
Туре	Snap switch control station
Packaging	
Carton	1
Weight Per each	8.2
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Power Distribution and Control
Enclosure	NEMA 3/7B/7C/7D/9E/9F/9G
standard	UL 1203, CSA C22.2