

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



EDSC2130 3-Way Switch Crouse-Hinds

Catalog Number	EDSC2130
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eds Snap Switch Control Station, 20A, With Switch, With Two 3/4" Hubs, Feraloy Iron Alloy, 1, Single-Gang, Three-Pole, 120-277V, Factory Sealed, Through Feed, 3-Way, 3/4", 120-277 Vac
Weight per unit	-
Product Category	Selector Switch Complete Assem
Features	
amperage rating	20
dimensions	
Material	FERALOY IRON ALLOY
Poles	3
Voltage Rating	120-277 VAC
Dimensions and Weight	
Size	5-7/8 In Length X 3-1/2 In Width X 2-11/16 In Height
Descriptions	
Description	3-WAY SWITCH
extra long description	CRS-H EDSC2130 EDS FS SELECTOR SWIT
Features	New EDSX series available with NEMA 4X protection for Class I, Division 2 hazardous areas.EDS/EDSX and EFD snap switches are used with magnetic starters or contactors for control of motors. Snap switch control stations are factory sealed to prevent arcing of the enclosed device from causing ignition of a hazardous atmosphere external to the enclosure. Factory sealing eliminates the need for external seals, simplifying installation and reducing material and labor costs.
Long Description	Eaton Crouse-Hinds series EDS snap switch control station, 20A, With switch, With two 3/4" hubs, Feraloy iron alloy, 1, Single-gang, Three-pole, 120-277V, Factory sealed, Through feed 3-way, 3/4", 120-277 Vac
Product Type	Eds FS Selector Switches
Special Features	Factory sealed



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	Eaton
GTIN	00782274765631
Manufacturers Part Number	EDSC2130
UPC	782274765631
Taxonomies, Classifications, and Cate	egories
Category Description	STANDARD DUTY PUSHBUTTONS (10250H-)
Туре	Snap switch control station
Packaging	
Carton	1
Weight Per each	8.45
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Power Distribution and Control
Enclosure	NEMA 3/7B/7C/7D/9E/9F/9G
standard	UL 1203, CSA C22.2