

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



EDSC218 3/4" 1G 2P Sel Switch Encl Crouse-Hinds

Catalog Number	EDSC218
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eds Snap Switch Control Station, 20A, With Switch, With Two 3/4" Hubs, Feraloy Iron Alloy, 1, Single-Gang, Two-Pole, 120-277V, Factory Sealed, Through Feed, Two-Pole, 3/4", 120-277 Vac
Weight per unit	
Product Category	
Features	
amperage rating	20A
dimensions	5.0600 IN X 3.5000 IN X 5.8750 IN
Material	FERALOY IRON ALLOY
Poles	Two-pole
Voltage Rating	120-277 VAC
Dimensions and Weight	
Size	5-7/8 In Length X 3-1/2 In Width X 2-11/16 In Height
Descriptions	
Description	3/4" 1G 2P SEL SWITCH ENCL
extra long description	CRS-H EDSC218 EDS FS GENERAL USE SN
Features	New EDSX series available with NEMA 4X protection for Class I, Division 2 hazardous areas.EDS/EDSX and EFD snap switches are used with magnetic starters or contactors for control of motors. Snap switch control stations are factory sealed to prevent arcing of the enclosed device from causing ignition of a hazardous atmosphere external to the enclosure. Factory sealing eliminates the need for external seals, simplifying installation and reducing material and labor costs.
Long Description	Eaton Crouse-Hinds series EDS snap switch control station, 20A, With switch, With two 3/4" hubs, Feraloy iron alloy, 1, Single-gang, Two-pole, 120-277V, Factory sealed, Through feed, Two-pole, 3/4", 120-277 Vac
Product Type	Eds FS General Use Snap Switches
Special Features	Factory sealed



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	Eaton
GTIN	00782274765280
Manufacturers Part Number	EDSC218
UPC	782274765280
Taxonomies, Classifications, and Cat	tegories
	STANDARD DUTY PUSHBUTTONS (10250H-)
Туре	Snap switch control station
Packaging	
Carton	1
Weight Per each	8.5
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Power Distribution and Control
Enclosure	NEMA 3/7B/7C/7D/9E/9F/9G
standard	UL 1203, CSA C22.2