

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### **EL19 1/2" 90D Female Cond Elbow** *Crouse-Hinds*

Catalog Number	EL19
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series El Elbow, Female, Feraloy Iron Alloy or Ductile Iron, 90°, 1/2"
Weight per unit	0.5000 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

#### **Features**

connection	Female Threaded
dimensions	1.2500 IN X 2.1600 IN X 2.1600 IN

#### **Descriptions**

Description	1/2" 90D FEMALE COND ELBOW
extra long description	CRS-H EL19 1/2 IRON NPT 90 DEG FEMA
Features	Crouse-Hinds series explosionproof unions are installed in rigid/IMC conduit systems to connect conduit to conduit, a conduit fitting, junction box or device enclosure. Expansion unions are also available, which allow for expansion and contraction of conduit and compensate for conduit cut too short. Available in a variety of materials, including stainless steel, to suit customer preferences. Explosionproof elbows allow for a 90° change in direction to the conduit run, or when terminating at a box or fit
Long Description	Eaton Crouse-Hinds series EL elbow, Female, Feraloy iron alloy or ductile iron, 90°, 1/2"
Product Type	1/2 Iron NPT 90 Deg Female Div 1 Elbow

#### **Manufacturer Information**

Brand	Eaton
GTIN	00782274307206
Manufacturers Part Number	EL19
UPC	782274307206

#### Taxonomies, Classifications, and Categories

Category Description	RIGID ELBOWS
Туре	ELBOW
dra artina ar	

### **Packaging**

Carton	1
Package	10
Weight Per each	0.5

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

#### **Uses, Certifications, and Standards**

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group A B C D, Class II Div 1 Group E F G, Class II
	Div 2 Group F G, Class III
standard	UL 886, CSA C22.2