

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



EL195 1/2 90D Male Cond Elbow *Crouse-Hinds*

Catalog Number	EL195	
Manufacturer	Crouse-Hinds	
Description	Eaton Crouse-Hinds Series El Elbow, Male, Feraloy Iron Alloy or Ductile Iron, 90°, 1/2"	
Weight per unit	0.2700 (lbs/each)	
Product Category	Rigid Conduit Fittings - Steel	
Features		
connection	Male Threaded	
dimensions	1.0600 IN X 1.9700 IN X 1.9700 IN	
Descriptions		
Description	1/2 90D MALE COND ELBOW	
extra long description	CRS-H EL195 1/2 NPT IRON 90 DEG MAL	
Features	Crouse-Hinds series explosionproof unions are installed in rigid/IMC conduit systems to connect conduit to conduit, a conduit fitting, junction box or device enclosure. Expansion unions are also available, which allow for expansion and contraction of conduit and compensate for conduit cut too short. Available in a variety of materials, including stainless steel, to suit customer preferences. Explosionproof elbows allow for a 90 change in direction to the conduit run, or when terminating at a box or fit	
Long Description	Eaton Crouse-Hinds series EL elbow, Male, Feraloy iron alloy or ductile iron, 90°, 1/2"	
Product Type	1/2 NPT Iron 90 Deg Male Div 1 Elbow	
Manufacturer Information		
Brand	Eaton	
GTIN	00782274307909	
Manufacturers Part Number	EL195	
UPC	782274307909	
Taxonomies, Classifications, and C	Categories	
Category Description	RIGID ELBOWS	

Taxo

Category Description	RIGID ELBOWS
Туре	ELBOW

Packaging

Carton	1	
Package	10	
Weight Per each	0.27	

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group A B C D, Class II Div 1 Group E F G, Class II
	Div 2 Group F G, Class III
standard	UL 886, CSA C22.2