

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Type

Carton

Package

Weight Per each

**Packaging** 

## EYD46 1-1/4" Fem/Male Drain Crouse-Hinds

Crouse-Hinds	
Catalog Number	EYD46
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eyd Conduit Sealing Fitting With Drain, Male and Female, Feraloy Iron Alloy and/or Ductile Iron, Vertical Only, 1-1/4"
Weight per unit	2.8 (lbs/each)
Product Category	Sealing Bodies
Features	
connection	Female Threaded, Female Threaded
dimensions	2.1900 IN X 2.1900 IN X 5.0600 IN
Material, Color, and Finish	
Finish	Untreated
Descriptions	
Description	1-1/4" FEM/MALE DRAIN
extra long description	CRS-H EYD46 1 1/4 EYD DRAIN SEAL MA
Features	In addition to restricting the passage of gases, vapors or flames from one portion of the electrical installation to another, Crouse-Hinds series EYD and EZD drain sealing fittings prevent accumulation of condensate above the seal. They are installed in vertical conduit runs and at low points in conduit systems.
Long Description	Eaton Crouse-Hinds series EYD conduit sealing fitting with drain, Male and female, Feraloy iron alloy and/or ductile iron, Vertical only, 1-1/4"
Product Type	1 1/4 Eyd Drain Seal Male-Female Hub
Special Features	With Drain, Vertical Position
Manufacturer Information	
Brand	Eaton
GTIN	00782274376301
Manufacturers Part Number	EYD46
UPC	782274376301
Taxonomies, Classifications, and C	Categories
Category Description	HAZARDOUS LOCATION FITTINGS
_	

Conduit sealing fitting with drain

2

2.75

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Uses, Certifications, and Standards**

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group C D, Class II Div 1 2 Group F G, Class III
standard	UL 886, CSA C22.2