

ELLIOT ELECTRIC SUPPLY Mar Deliver Lower Cost Quality Products, & Personal Service 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



EYSR6 2" Cond Seal Crouse-Hinds

o	
Catalog Number	EYSR6
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eysr Retrofit Sealing Fitting, Feraloy Iron Alloy, 2"
Weight per unit	7.5 (lbs/each)
Product Category	Sealing Bodies
atures	
dimensions	6.2500 IN X 3.0000 IN X 4.0000 IN
Material	FERALOY IRON ALLOY
aterial, Color, and Finish Finish	Electrogalvanized With Aluminum Acrylic Painted
mensions and Weight Size	2 in
	<u>ح ۱۱۱</u>
escriptions	
Construction	Explosionproof, Dust Ignitionproof
Description	2" COND SEAL
extra long description	CRS-H EYSR6 2 RETROFIT SEALING FTG
Features	Crouse-Hinds series EYSR retrofit sealing fittings are installed in rigid metal conduit systems in Class I, Division 2 hazardous
	locations to replace installed Eaton's Crouse-Hinds series EYS o
	EYD sealing fittings. EYSRs allow the replacement to be done
	without disassembly of the conduit system, and they can be
	installed in vertical or horizontal positions, indoors or outdoors
	As with all sealing fittings, EYSRs restrict the passage of gases,
	vapors or flames from one portion of the electrical install
Long Description	Eaton Crouse-Hinds series EYSR retrofit sealing fitting, Feraloy iron alloy, 2"
Product Type	2 Detection FTC ($1/4$ V 4 V 2
Special Features	Horizontal/Vertical Position
anufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274793436
Manufacturers Part Number	EYSR6
UPC	782274793436
xonomies, Classifications, and (Categories
	HAZARDOUS LOCATION FITTINGS
	Retrofit sealing fitting



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton	1
Weight Per each	7.45
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group C D, Class II Div 1 2 Group E F G
standard	UL 886, CSA C22.2