



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



EYSX3SA 1" Alu Cond Seal *Crouse-Hinds*

| | |
|------------------|--|
| Catalog Number | EYSX3SA |
| Manufacturer | Crouse-Hinds |
| Description | Eaton Crouse-Hinds Series Eysx Expanded Fill Sealing Fitting, Female, Copper-Free Aluminum, Vertical or Horizontal, 1" |
| Weight per unit | 0.6000 (lbs/each) |
| Product Category | Aluminum |

Features

| | |
|------------|-----------------------------------|
| dimensions | 2.1900 IN X 2.1900 IN X 5.0600 IN |
|------------|-----------------------------------|

Descriptions

| | |
|------------------------|---|
| Description | 1" ALU COND SEAL |
| extra long description | CRS-H EYSX3 SA 1 AL FEM VERT/HORZ E |
| Features | EYSX expanded fill sealing fittings from Eaton Crouse-Hinds Division provide 40% wire fill capacity to allow uninterrupted runs in a conduit system. They are designed to restrict the passage of gases, vapors or flames from one portion of the electrical installation to another, limit explosions to the sealed off enclosure, and limit pre-compression or "pressure piling" in conduit systems. EYSX expanded fill sealing fittings are available for installation in both horizontal or vertical positions. |
| Long Description | Eaton Crouse-Hinds series EYSX expanded fill sealing fitting, Female, Copper-free aluminum, Vertical or horizontal, 1" |
| Product Type | 1 Al Fem Vert/Horz Expand Fill Seal FT |

Manufacturer Information

| | |
|---------------------------|---------------------------|
| Brand | EATON CROUSE-HINDS SERIES |
| GTIN | 00782274943190 |
| Manufacturers Part Number | EYSX3 SA |
| UPC | 782274943190 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-------------------------------|
| Category Description | HAZARDOUS LOCATION FITTINGS |
| Type | Expanded fill sealing fitting |

Packaging

| | |
|-----------------|-----|
| Carton | 1 |
| Package | 2 |
| Weight Per each | 0.6 |

Uses, Certifications, and Standards

| | |
|-------------|--|
| Application | Ind Facilities & Factories - Industrial Facilities/Factories - Other |
| standard | UL 886, CSA C22.2 |