



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



F1.5X3LG6 1.5" X 3" Slotted Wiring Duct, Light Gray *Panduit Corporation*

| | |
|------------------|--|
| Catalog Number | F1.5X3LG6 |
| Manufacturer | Panduit Corporation |
| Description | The F1.5X3LG6 Panduct Lead-Free PVC Narrow Slot Wiring Duct Features A Narrow Slot/Finger Design That Closely Matches The Spacing Of High-Density Components. Upper and Lower Scorelines Allow For Easy Finger/Sidewall Section Removal. UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use Temperature Up to 122°F (50°C). Mounting Holes Provided. Lead-Free PVC. 1.5" X 3" (38.1 MM X 76.2 MM) and 6' (1.83 M) Long. Cover Sold Separately. Color Light Gray. |
| Weight per unit | 0.3359 (lbs/each) |
| Product Category | Ducts, Raceways, Runways, Tray |

Features

| | |
|------------|----------------|
| connection | Mounting Holes |
| Material | PVC |
| media | Yes |

Material, Color, and Finish

| | |
|-------|------|
| Color | Gray |
|-------|------|

Dimensions and Weight

| | |
|--------|-------------|
| Height | 3.12 |
| Length | NA |
| Size | 1.50 x 3.00 |
| Width | 1.75 |

Descriptions

| | |
|------------------------|--|
| Description | 1.5" X 3" SLOTTED WIRING DUCT, LIGHT GRAY |
| extra long description | PAN F1.5X3LG6 Panduct® F1.5X3LG6 Ba |
| Long Description | The F1.5X3LG6 Panduct Lead-Free PVC Narrow Slot Wiring Duct features a narrow slot/finger design that closely matches the spacing of high-density components. Upper and lower scorelines allow for easy finger/sidewall section removal. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Mounting holes provided. Lead-free PVC. 1.5" x 3" (38.1 mm x 76.2 mm) and 6' (1.83 m) long. Cover sold separately. Color Light Gray. |
| Product Type | Panduct® F1.5X3LG6 Base Wiring Duct |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | PANDUIT |
| GTIN | 00074983375370 |
| Manufacturers Part Number | F1.5X3LG6 |
| UPC | 074983375370 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|----------------------|
| Category Description | WIRE DUCT AND COVERS |
| Type | Base Wiring Duct |

Availability

| | |
|-------------|---|
| minimum qty | 6 |
|-------------|---|

Packaging

| | |
|-----------------|--------|
| Carton | 6 |
| Package | 120 |
| Weight Per foot | 0.3359 |

Uses, Certifications, and Standards

| | |
|-------------|--|
| Application | Narrow slot/finger design provides more slots to fit the spacing of high-density terminal block applications |
| standard | CSA Approved;RoHS Compliant, UL Recognized, CE Compliant |