




# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## F1.5X3LG6 1.5" X 3" Slotted Wiring Duct, Light Gray Panduit Corporation

Catalog Number	F1.5X3LG6
Manufacturer	Panduit Corporation
Description	The F1.5X3LG6 Panduct Lead-Free PVC Narrow Slot Wiring Duct Features A Narrow Slot/Finger Design That Closely Matches The Spacing Of High-Density Components. Upper and Lower Scorelines Allow For Easy Finger/Sidewall Section Removal. UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use Temperature Up to 122°F (50°C). Mounting Holes Provided. Lead-Free PVC. 1.5" X 3" (38.1 MM X 76.2 MM) and 6' (1.83 M) Long. Cover Sold Separately. Color Light Gray.
Weight per unit	0.3359 (lbs/each)
Product Category	Ducts, Raceways, Runways, Tray

### Features

connection	Mounting Holes
Material	PVC
media	Yes

### Material, Color, and Finish

Color	Light Gray
-------	------------

### Dimensions and Weight

Height	3.12
Length	NA
Size	1.50 x 3.00
Width	1.75

### Descriptions

Description	1.5" X 3" SLOTTED WIRING DUCT, LIGHT GRAY
extra long description	PAN F1.5X3LG6 Panduct® F1.5X3LG6 Ba
Long Description	The F1.5X3LG6 Panduct Lead-Free PVC Narrow Slot Wiring Duct features a narrow slot/finger design that closely matches the spacing of high-density components. Upper and lower scorelines allow for easy finger/sidewall section removal. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Mounting holes provided. Lead-free PVC. 1.5" x 3" (38.1 mm x 76.2 mm) and 6' (1.83 m) long. Cover sold separately. Color Light Gray.
Product Type	Panduct® F1.5X3LG6 Base Wiring Duct



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Manufacturer Information

Brand	PANDUIT
GTIN	00074983375370
Manufacturers Part Number	F1.5X3LG6
UPC	074983375370

## Taxonomies, Classifications, and Categories

Category Description	WIRE DUCT AND COVERS
Type	Base Wiring Duct

## Availability

minimum qty	6
-------------	---

## Packaging

Carton	6
Package	120
Weight Per foot	0.3359

## Uses, Certifications, and Standards

Application	Narrow slot/finger design provides more slots to fit the spacing of high-density terminal block applications
standard	RoHS Compliant, UL Recognized, CE Compliant; CSA Approved