



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## F1X1WH6 1X1X72" WHT NM Slot Duct *Panduit Corporation*

Catalog Number	F1X1WH6
Manufacturer	Panduit Corporation
Description	The F1X1WH6 Panduct Lead-Free PVC Narrow Slot Wiring Duct Features A Narrow Slot/Finger Design That Closely Matches The Spacing Of High-Density Components. Upper and Lower Scorelines Allow For Easy Finger/Sidewall Section Removal. UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use Temperature Up to 122°F (50°C). Mounting Holes Provided. Lead-Free PVC. 1" X 1" (25.4 MM X 25.4 MM) and 6' (1.83 M) Long. Cover Sold Separately. Color White.
Weight per unit	0.1070 (lbs/each)
Product Category	Ducts, Raceways, Runways, Tray

### Features

connection	Mounting Holes
Material	PVC
media	Yes

### Material, Color, and Finish

Color	White
-------	-------

### Dimensions and Weight

Height	1.13
Length	NA
Size	1.00 x 1.00
Width	1.25

### Descriptions

Description	1X1X72" WHT NM SLOT DUCT
extra long description	PAN F1X1WH6 Panduct® F1X1WH6 Base W
Long Description	The F1X1WH6 Panduct Lead-Free PVC Narrow Slot Wiring Duct features a narrow slot/finger design that closely matches the spacing of high-density components. Upper and lower scorelines allow for easy finger/sidewall section removal. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Mounting holes provided. Lead-free PVC. 1" x 1" (25.4 mm x 25.4 mm) and 6' (1.83 m) long. Cover sold separately. Color White.
Product Type	Panduct® F1X1WH6 Base Wiring Duct



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Manufacturer Information

Brand	PANDUIT
GTIN	00074983375028
Manufacturers Part Number	F1X1WH6
UPC	074983375028

## Taxonomies, Classifications, and Categories

Category Description	WIRE DUCT AND COVERS
Type	Base Wiring Duct

## Availability

minimum qty	6
-------------	---

## Packaging

Carton	6
Package	120
Weight Per foot	0.107

## Uses, Certifications, and Standards

Application	Narrow slot/finger design provides more slots to fit the spacing of high-density terminal block applications
standard	CSA Approved;RoHS Compliant, UL Recognized, CE Compliant