Pass and Seymour

Flexcor® Support Grips Service and Bus Drop, Single Eye, Cable Diameter 0.53 - 0.73 in.

Part No. FC52



FC52: Bus Drop, Closed Mesh, Single Eye, Cable Diameter 0.53 - 0.73 inches, Bale Length 9-in, Mesh Length 6.5-in, Break Strength 1100 lbs.

Features & Benefits

Bus drop grips are used as cable support. They relieve any direct tension from the critical connection and absorb vibration and flexing.

They are offered with either the single eye or locking bale attachment.

Most Flexcor products have UL and/or CSA approvals. Please contact factory for approval information.

Bus drop grips are woven of galvanized steel wire.

Support grips are woven of corrosion-resistant tinned-stainless steel wire.

Bale Length: 9: Mesh Length: 6.5

Specifications

General Info

Product Line	Pass & Seymour	UPC Number	785007998733
Country Of Origin	Mexico	Construction	Various Types of Pulling, Support and Strain Relief Grips
Application Sector	Industrial	Standard	UL/CSA Approval (consult factory)
Type	Support Grip		

Dimensions

Product Width US	0.73 in	Product Length US	6.5 in
Mesh Length	6.5 in	Cable Diameter Range	0.530-0.730 in

Listing Agencies / 3rd Party Agencies

CSA Listed	Yes	CSA File Number	67507

Technical Information

Approximate Break Strength	1100 lb	Maximum Cable Range	0.53 in
Eye Style	Single	Minimum Cable Range	0.73 in
Capacity	Various Cable Diameter Ranges	Indoor/Outdoor	Both

Mounting	Consult the Factory for Mounting Recommendations

Pass and Seymour

Flexcor® Support Grips Service and Bus Drop, Single Eye, Cable Diameter 0.53 - 0.73 in.

Part No. FC52



FC52: Bus Drop, Closed Mesh, Single Eye, Cable Diameter 0.53 - 0.73 inches, Bale Length 9-in, Mesh Length 6.5-in, Break Strength 1100 lbs.

Features & Benefits

Bus drop grips are used as cable support. They relieve any direct tension from the critical connection and absorb vibration and flexing.

They are offered with either the single eye or locking bale attachment.

Most Flexcor products have UL and/or CSA approvals. Please contact factory for approval information.

Bus drop grips are woven of galvanized steel wire.

Support grips are woven of corrosion-resistant tinned-stainless steel wire.

Bale Length: 9: Mesh Length: 6.5

Specifications

General Info

Product Line	Pass & Seymour	UPC Number	785007998733
Country Of Origin	Mexico	Construction	Various Types of Pulling, Support and Strain Relief Grips
Application Sector	Industrial	Standard	UL/CSA Approval (consult factory)
Type	Support Grip		

Dimensions

Product Width US	0.73 in	Product Length US	6.5 in
Mesh Length	6.5 in	Cable Diameter Range	0.530-0.730 in

Listing Agencies / 3rd Party Agencies

CSA Listed	Yes	CSA File Number	67507

Technical Information

Approximate Break Strength	1100 lb	Maximum Cable Range	0.53 in
Eye Style	Single	Minimum Cable Range	0.73 in
Capacity	Various Cable Diameter Ranges	Indoor/Outdoor	Both

Mounting	Consult the Factory for Mounting Recommendations