

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FNQR30 30A 600V TD Class CC Fuse Bussmann Fuses

| Catalog Number | FNQR30 |
|---------------------------------|---|
| Catalog Number Manufacturer | Bussmann Fuses |
| Description | Fuse, Time Delay Fuse Speed, Class CC Fuse, 12 S @ 200% |
| Description | Response Time, Ferrule End X Ferrule End Connection, 30 A, 600 |
| | V Ac, Melamine Material, 0.41 In Diameter, 1.5 In Overall Length |
| | 0.02 LB |
| Weight per unit | 0.0200 (lbs/each) |
| Product Category | Small Dimension Fuses |
| eatures | |
| amperage rating | 30 |
| class | Class CC |
| connection | Ferrule End X Ferrule End |
| dimensions | 1.5000 IN X 0.4100 IN X 0.4100 IN |
| media | Voc |
| Dimensions and Weight | |
| Size | 13/32 In Diameter X 1-1/2 In Length |
| escriptions | |
| Description | 30A 600V TD CLASS CC FUSE |
| extra long description | BUSS FNQ-R-30 CLASS CC TIME DELAY |
| Features | Bussmann's Class CC fuses set the standard in Class CC fuse |
| | performance in the industry. Recognized for their superior |
| | performance, Bussmann has the right product for your circuit |
| | and equipment protection needs. These branch circuit rated, |
| | 600v, 200,000a IR fuses offer exceptional protection in the |
| | smallest package of any UL class of fuses. Choose from the |
| | ultimate protection provided by our Low Peak LP-CC fuses, the |
| | time delay of our FNQ-R's for your control transformer and similar control applications or |
| Special Features | Dejection Style |
| Anufacturer Information | |
| Brand | Eaton |
| GTIN | 00051712497145 |
| UPC | 051712497145 |
| axonomies, Classifications, and | |
| Category Description | |
| Туре | FUSE |



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

| Carton | 10 |
|-------------------------------------|------|
| Weight Per each | 0.02 |
| Uses, Certifications, and Standards | |

standard

RoHS Compliant, CE Marked