

Electrical Power Fuses



Type BAN 13/32" x 1-1/2" (10.3 mm X 38.1 mm) Fast Acting

Fiber; Formerly 5AB. Mounts in Buss fuseholders, fuseblocks, and clips. Rated at 250V.



| Mfr.'s Type & Amp Rating | Each | Mfr.'s Type & Amp Rating | Each |
|--------------------------|------|--------------------------|------|
| BAN-1 | 2.98 | BAN-10 | 2.84 |
| BAN-2 | 2.98 | BAN-12 | 2.98 |
| BAN-3 | 2.98 | BAN-15 | 2.84 |
| BAN-4 | 2.98 | BAN-20 | 2.84 |
| BAN-5 | 2.98 | BAN-25 | 2.98 |
| BAN-6 | 2.98 | BAN-30 | 2.68 |
| BAN-8 | 2.98 | | |

Type FNM 13/32" x 1-1/2" (10.3mm x 38.1mm) Time-Delay

Fiber. Formerly designed 5AG. A Dual element Fusetron fuse. For circuits with high inrush currents. Mount in Buss fuseholders, fuseblocks, and clips. U.L. File E19180; guide JDYX. CSA File 53787; Class 1422-01. Rated at 250 V to 10 A, 125V, 12-15 A and 32 V, 20-30A.



| Mfr.'s Type & Amp Rating | Each | Mfr.'s Type & Amp Rating | Each |
|--------------------------|------|--------------------------|------|
| FNM-1/10 | 5.94 | FNM-2-8/10 | 5.50 |
| FNM-15/100 | 5.94 | FNM-3 | 4.30 |
| FNM-2/10 | 5.94 | FNM-3-2/10 | 4.40 |
| FNM-1/4 | 5.94 | FNM-3-1/2 | 4.40 |
| FNM-3/10 | 5.94 | FNM-4 | 4.30 |
| FNM-4/10 | 5.94 | FNM-4-1/2 | 5.50 |
| FNM-1/2 | 4.78 | FNM-5 | 4.12 |
| FNM-6/10 | 4.78 | FNM-5-6/10 | 5.50 |
| FNM-8/10 | 4.78 | FNM-6 | 4.64 |
| FNM-1 | 4.50 | FNM-6-1/4 | 4.40 |
| FNM-1-1/8 | 5.94 | FNM-7 | 4.40 |
| FNM-1-1/4 | 5.32 | FNM-8 | 4.30 |
| FNM-1-4/10 | 5.70 | FNM-9 | 5.50 |
| FNM-1-1/2 | 5.00 | FNM-10 | 4.12 |
| FNM-1-6/10 | 5.00 | FNM-12 | 4.64 |
| FNM-1- 8/10 | 5.50 | FNM-15 | 4.12 |
| FNM-2 | 4.12 | FNM-20 | 4.30 |
| FNM-2-1/4 | 5.30 | FNM-25 | 4.90 |
| FNM-2-1/2 | 4.64 | FNM-30 | 4.30 |

Type FNW 13/32" x 1-1/2" (10.3mm x 38.1mm) Time-Delay

Melamine. Interrupting rating - 10,000AIC. Mount in Buss fuseholders, fuseblocks, and clips. U.L. File E19180; Guide JDYX. Rated at 250 V.



| Mfr.'s Type & Amp Rating | Each | Mfr.'s Type & Amp Rating | Each |
|--------------------------|------|--------------------------|------|
| FNW-12 | 4.90 | FNW-25 | 4.90 |
| FNW-15 | 4.48 | FNW-30 | 4.48 |
| FNW-20 | 4.48 | | |

Type KTK-R 13/32 x 1-1/2" (10.3mm x 38.1mm) Fast Acting, Class CC, Rejection Type

A Limitron fast acting fuse Melamine. U.L. Listed for branch circuit protection. Class CC. Rejection type; for both standard holders or those which reject other type fuses. Mount in Buss Class CC fuseblocks and Buss fuseholders HPS-RR (thru 30 amps). Interrupting rating - 200,000AIC. Current limiting. U.L. File 4273A; Guide JDDZ. CSA File 53787; Class 12422-01. Rated at 600 V.



| Mfr.'s Type & Amp Rating | Each | Mfr.'s Type & Amp Rating | Each |
|--------------------------|-------|--------------------------|-------|
| KTK-R-1/10 | 14.06 | KTK-R-4 | 11.24 |
| KTK-R-1/8 | 14.06 | KTK-R-5 | 10.54 |
| KTK-R-2/10 | 14.06 | KTK-R-6 | 11.06 |
| KTK-R-1/4 | 14.06 | KTK-R-7 | 12.90 |
| KTK-R-3/10 | 14.06 | KTK-R-8 | 11.24 |
| KTK-R-4/10 | 14.06 | KTK-R-9 | 14.16 |
| KTK-R-1/2 | 11.16 | KTK-R-10 | 10.54 |
| KTK-R-3/4 | 12.14 | KTK-R-12 | 10.72 |
| KTK-R-1 | 10.54 | KTK-R-15 | 10.54 |
| KTK-R-1-1/12 | 10.54 | KTK-R-20 | 10.54 |
| KTK-R-2 | 10.54 | KTK-R-25 | 11.24 |
| KTK-R-3 | 10.54 | KTK-R-30 | 10.54 |

Type FNQ 13/32" x 1-1/2" (10.3mm x 38.1mm) Time-Delay

Fiber. Interrupting rating - 10,000AIC. Mount in Buss fuseholders, fuseblocks, and clips. U.L. File E19180; Guide JDYX. CSA File 53787; Class 1422-01. Rated at 500 V.



| Mfr.'s Type & Amp Rating | Each | Mfr.'s Type & Amp Rating | Each |
|--------------------------|-------|--------------------------|-------|
| FNQ-1/10 | 14.64 | FNQ-3-2/10 | 12.38 |
| FNQ-1/8 | 14.78 | FNQ-3-1/2 | 13.36 |
| FNQ-15/100 | 15.38 | FNQ-4 | 11.82 |
| FNQ-2/10 | 14.78 | FNQ-4-1/2 | 14.36 |
| FNQ-1/4 | 13.36 | FNQ-5 | 11.82 |
| FNQ-3/10 | 14.78 | FNQ-5-6/10 | 14.36 |
| FNQ-4/10 | 14.78 | FNQ-6 | 11.82 |
| FNQ-1/2 | 12.38 | FNQ-6-1/4 | 15.22 |
| FNQ-6/10 | 13.36 | FNQ-7 | 12.38 |
| FNQ-8/10 | 13.36 | FNQ-8 | 11.82 |
| FNQ-1 | 11.82 | FNQ-9 | 15.22 |
| FNQ-1-1/8 | 15.54 | FNQ-10 | 11.82 |
| FNQ-1-1/4 | 14.36 | FNQ-12 | 11.82 |
| FNQ-1-1/2 | 12.38 | FNQ-14 | 15.84 |
| FNQ-1-6/10 | 12.38 | FNQ-15 | 11.82 |
| FNQ-2 | 11.82 | FNQ-20 | 11.82 |
| FNQ-2-1/4 | 15.22 | FNQ-25 | 11.82 |
| FNQ-2-1/2 | 12.38 | FNQ-30 | 11.82 |
| FNQ-3 | 11.82 | | |

Type SC 13/32" x 1-5/16" (to 2-1/4") Time-Delay (Except SC-1/2 to SC -6)

Highly compact branch circuit fuses; U.L. Class G. Applicable in 120/208, 120/240, and 277/480 volt circuits. Interrupting rating - 100,000AIC. Current limiting. Mount in type HPF fuseholders; also Buss Class G fuseblocks. Size varies with amp rating; prevent oversizing. For full information please call any of the toll free numbers on the back of this catalog and request Buss Catalog FLC. U.L. File E4273A; Guide JDDZ. Rated at 300 V.



| Mfr.'s Type & Amp Rating | Each | Mfr.'s Type & Amp Rating | Each |
|--------------------------|------|--------------------------|------|
| SC-1/2 | 6.08 | SC-15 | 3.76 |
| SC-1 | 5.46 | SC-20 | 3.96 |
| SC-2 | 5.46 | SC-25 | 9.04 |
| SC-3 | 5.46 | SC-30 | 7.04 |
| SC-4 | 5.36 | SC-35 | 8.36 |
| SC-5 | 5.12 | SC-40 | 7.80 |
| SC-6 | 5.12 | SC-45 | 8.86 |
| SC-8 | 6.08 | SC-50 | 8.86 |
| SC-10 | 5.12 | SC-60 | 7.66 |

Type KTK 13/32" x 1-1/2" (10.3mm x 38.1mm) Fast Acting

A Limitron fast acting fuse Melamine. Interrupting rating 100,000 AIC. Mount in Buss fuseholders, fuseblocks, and clips. U.L. File E 19180; Guide JDYX CSA File 53787; Class 1422-01. Rated at 600V.



| Mfr.'s Type & Amp Rating | Each | Mfr.'s Type & Amp Rating | Each |
|--------------------------|-------|--------------------------|-------|
| KTK-1/10 | 12.28 | KTK-4 | 10.06 |
| KTK-1/8 | 12.82 | KTK-5 | 9.86 |
| KTK-2/10 | 12.82 | KTK-6 | 8.58 |
| KTK-1/4 | 10.82 | KTK-7 | 11.62 |
| KTK-3/10 | 12.82 | KTK-8 | 10.06 |
| KTK-1/2 | 10.62 | KTK-9 | 12.82 |
| KTK-3/4 | 11.62 | KTK-10 | 9.86 |
| KTK-1 | 9.86 | KTK-12 | 11.58 |
| KTK-1-1/2 | 10.72 | KTK-15 | 9.86 |
| KTK-2 | 9.86 | KTK-20 | 9.90 |
| KTK-2-1/2 | 12.28 | KTK-25 | 9.90 |
| KTK-3 | 9.86 | KTK-30 | 9.90 |
| KTK-3-1/2 | 12.82 | | |

Type FNQ-R 13/32" x 1-1/2" (10.3mm x 38.1mm) Time-Delay, Class CC, Rejection Type

Construction: Melamine tube. Voltage Rating: 600 VAC. Interrupting Rating: 200,000A RMS Sym. Approvals: Std. 248-4, Class CC; UL Listed, Guide JDDZ, File E4273; CSA Certified, Class 1422-01, File 53787.



| Mfr.'s Type & Amp Rating | Each | Mfr.'s Type & Amp Rating | Each |
|--------------------------|-------|--------------------------|-------|
| FNQ-R-1/4 | 14.10 | FNQ-R-2-1/2 | 14.10 |
| FNQ-R-4/10 | 15.60 | FNQ-R-3 | 12.54 |
| FNQ-R-1/2 | 12.54 | FNQ-R-4 | 13.54 |
| FNQ-R-6/10 | 15.60 | FNQ-R-5 | 12.66 |
| FNQ-R-8/10 | 13.88 | FNQ-R-6 | 14.10 |
| FNQ-R-1 | 12.38 | FNQ-R-7-1/2 | 14.90 |
| FNQ-R-1-1/2 | 12.66 | FNQ-R-8 | 14.10 |
| FNQ-R-2 | 12.66 | FNQ-R-10 | 13.54 |



CBC is a full line BUSSMANN distributor. Consult us for complete information on products not shown in this catalog.

Electrical Power Fuses



Type BAN 13/32" x 1-1/2" (10.3 mm X 38.1 mm) Fast Acting

Fiber; Formerly 5AB. Mounts in Buss fuseholders, fuseblocks, and clips. Rated at 250V.



| Mfr.'s Type & Amp Rating | Each | Mfr.'s Type & Amp Rating | Each |
|--------------------------|------|--------------------------|------|
| BAN-1 | 2.98 | BAN-10 | 2.84 |
| BAN-2 | 2.98 | BAN-12 | 2.98 |
| BAN-3 | 2.98 | BAN-15 | 2.84 |
| BAN-4 | 2.98 | BAN-20 | 2.84 |
| BAN-5 | 2.98 | BAN-25 | 2.98 |
| BAN-6 | 2.98 | BAN-30 | 2.68 |
| BAN-8 | 2.98 | | |

Type FNM 13/32" x 1-1/2" (10.3mm x 38.1mm) Time-Delay

Fiber. Formerly designed 5AG. A Dual element Fusetron fuse. For circuits with high inrush currents. Mount in Buss fuseholders, fuseblocks, and clips. U.L. File E19180; guide JDYX. CSA File 53787; Class 1422-01. Rated at 250 V to 10 A, 125V, 12-15 A and 32 V, 20-30A.



| Mfr.'s Type & Amp Rating | Each | Mfr.'s Type & Amp Rating | Each |
|--------------------------|------|--------------------------|------|
| FNM-1/10 | 5.94 | FNM-2-8/10 | 5.50 |
| FNM-15/100 | 5.94 | FNM-3 | 4.30 |
| FNM-2/10 | 5.94 | FNM-3-2/10 | 4.40 |
| FNM-1/4 | 5.94 | FNM-3-1/2 | 4.40 |
| FNM-3/10 | 5.94 | FNM-4 | 4.30 |
| FNM-4/10 | 5.94 | FNM-4-1/2 | 5.50 |
| FNM-1/2 | 4.78 | FNM-5 | 4.12 |
| FNM-6/10 | 4.78 | FNM-5-6/10 | 5.50 |
| FNM-8/10 | 4.78 | FNM-6 | 4.64 |
| FNM-1 | 4.50 | FNM-6-1/4 | 4.40 |
| FNM-1-1/8 | 5.94 | FNM-7 | 4.40 |
| FNM-1-1/4 | 5.32 | FNM-8 | 4.30 |
| FNM-1-4/10 | 5.70 | FNM-9 | 5.50 |
| FNM-1-1/2 | 5.00 | FNM-10 | 4.12 |
| FNM-1-6/10 | 5.00 | FNM-12 | 4.64 |
| FNM-1- 8/10 | 5.50 | FNM-15 | 4.12 |
| FNM-2 | 4.12 | FNM-20 | 4.30 |
| FNM-2-1/4 | 5.30 | FNM-25 | 4.90 |
| FNM-2-1/2 | 4.64 | FNM-30 | 4.30 |

Type FNW 13/32" x 1-1/2" (10.3mm x 38.1mm) Time-Delay

Melamine. Interrupting rating - 10,000AIC. Mount in Buss fuseholders, fuseblocks, and clips. U.L. File E19180; Guide JDYX. Rated at 250 V.



| Mfr.'s Type & Amp Rating | Each | Mfr.'s Type & Amp Rating | Each |
|--------------------------|------|--------------------------|------|
| FNW-12 | 4.90 | FNW-25 | 4.90 |
| FNW-15 | 4.48 | FNW-30 | 4.48 |
| FNW-20 | 4.48 | | |

Type KTK-R 13/32 x 1-1/2" (10.3mm x 38.1mm) Fast Acting, Class CC, Rejection Type

A Limitron fast acting fuse Melamine. U.L. Listed for branch circuit protection. Class CC. Rejection type; for both standard holders or those which reject other type fuses. Mount in Buss Class CC fuseblocks and Buss fuseholders HPS-RR (thru 30 amps). Interrupting rating - 200,000AIC. Current limiting. U.L. File 4273A; Guide JDDZ. CSA File 53787; Class 12422-01. Rated at 600 V.



| Mfr.'s Type & Amp Rating | Each | Mfr.'s Type & Amp Rating | Each |
|--------------------------|-------|--------------------------|-------|
| KTK-R-1/10 | 14.06 | KTK-R-4 | 11.24 |
| KTK-R-1/8 | 14.06 | KTK-R-5 | 10.54 |
| KTK-R-2/10 | 14.06 | KTK-R-6 | 11.06 |
| KTK-R-1/4 | 14.06 | KTK-R-7 | 12.90 |
| KTK-R-3/10 | 14.06 | KTK-R-8 | 11.24 |
| KTK-R-4/10 | 14.06 | KTK-R-9 | 14.16 |
| KTK-R-1/2 | 11.16 | KTK-R-10 | 10.54 |
| KTK-R-3/4 | 12.14 | KTK-R-12 | 10.72 |
| KTK-R-1 | 10.54 | KTK-R-15 | 10.54 |
| KTK-R-1-1/12 | 10.54 | KTK-R-20 | 10.54 |
| KTK-R-2 | 10.54 | KTK-R-25 | 11.24 |
| KTK-R-3 | 10.54 | KTK-R-30 | 10.54 |

Type FNQ 13/32" x 1-1/2" (10.3mm x 38.1mm) Time-Delay

Fiber. Interrupting rating - 10,000AIC. Mount in Buss fuseholders, fuseblocks, and clips. U.L. File E19180; Guide JDYX. CSA File 53787; Class 1422-01. Rated at 500 V.



| Mfr.'s Type & Amp Rating | Each | Mfr.'s Type & Amp Rating | Each |
|--------------------------|-------|--------------------------|-------|
| FNQ-1/10 | 14.64 | FNQ-3-2/10 | 12.38 |
| FNQ-1/8 | 14.78 | FNQ-3-1/2 | 13.36 |
| FNQ-15/100 | 15.38 | FNQ-4 | 11.82 |
| FNQ-2/10 | 14.78 | FNQ-4-1/2 | 14.36 |
| FNQ-1/4 | 13.36 | FNQ-5 | 11.82 |
| FNQ-3/10 | 14.78 | FNQ-5-6/10 | 14.36 |
| FNQ-4/10 | 14.78 | FNQ-6 | 11.82 |
| FNQ-1/2 | 12.38 | FNQ-6-1/4 | 15.22 |
| FNQ-6/10 | 13.36 | FNQ-7 | 12.38 |
| FNQ-8/10 | 13.36 | FNQ-8 | 11.82 |
| FNQ-1 | 11.82 | FNQ-9 | 15.22 |
| FNQ-1-1/8 | 15.54 | FNQ-10 | 11.82 |
| FNQ-1-1/4 | 14.36 | FNQ-12 | 11.82 |
| FNQ-1-1/2 | 12.38 | FNQ-14 | 15.84 |
| FNQ-1-6/10 | 12.38 | FNQ-15 | 11.82 |
| FNQ-2 | 11.82 | FNQ-20 | 11.82 |
| FNQ-2-1/4 | 15.22 | FNQ-25 | 11.82 |
| FNQ-2-1/2 | 12.38 | FNQ-30 | 11.82 |
| FNQ-3 | 11.82 | | |

Type SC 13/32" x 1-5/16" (to 2-1/4") Time-Delay (Except SC-1/2 to SC -6)

Highly compact branch circuit fuses; U.L. Class G. Applicable in 120/208, 120/240, and 277/480 volt circuits. Interrupting rating - 100,000AIC. Current limiting. Mount in type HPF fuseholders; also Buss Class G fuseblocks. Size varies with amp rating; prevent oversizing. For full information please call any of the toll free numbers on the back of this catalog and request Buss Catalog FLC. U.L. File E4273A; Guide JDDZ. Rated at 300 V.



| Mfr.'s Type & Amp Rating | Each | Mfr.'s Type & Amp Rating | Each |
|--------------------------|------|--------------------------|------|
| SC-1/2 | 6.08 | SC-15 | 3.76 |
| SC-1 | 5.46 | SC-20 | 3.96 |
| SC-2 | 5.46 | SC-25 | 9.04 |
| SC-3 | 5.46 | SC-30 | 7.04 |
| SC-4 | 5.36 | SC-35 | 8.36 |
| SC-5 | 5.12 | SC-40 | 7.80 |
| SC-6 | 5.12 | SC-45 | 8.86 |
| SC-8 | 6.08 | SC-50 | 8.86 |
| SC-10 | 5.12 | SC-60 | 7.66 |

Type KTK 13/32" x 1-1/2" (10.3mm x 38.1mm) Fast Acting

A Limitron fast acting fuse Melamine. Interrupting rating 100,000 AIC. Mount in Buss fuseholders, fuseblocks, and clips. U.L. File E 19180; Guide JDYX CSA File 53787; Class 1422-01. Rated at 600V.



| Mfr.'s Type & Amp Rating | Each | Mfr.'s Type & Amp Rating | Each |
|--------------------------|-------|--------------------------|-------|
| KTK-1/10 | 12.28 | KTK-4 | 10.06 |
| KTK-1/8 | 12.82 | KTK-5 | 9.86 |
| KTK-2/10 | 12.82 | KTK-6 | 8.58 |
| KTK-1/4 | 10.82 | KTK-7 | 11.62 |
| KTK-3/10 | 12.82 | KTK-8 | 10.06 |
| KTK-1/2 | 10.62 | KTK-9 | 12.82 |
| KTK-3/4 | 11.62 | KTK-10 | 9.86 |
| KTK-1 | 9.86 | KTK-12 | 11.58 |
| KTK-1-1/2 | 10.72 | KTK-15 | 9.86 |
| KTK-2 | 9.86 | KTK-20 | 9.90 |
| KTK-2-1/2 | 12.28 | KTK-25 | 9.90 |
| KTK-3 | 9.86 | KTK-30 | 9.90 |
| KTK-3-1/2 | 12.82 | | |

Type FNQ-R 13/32" x 1-1/2" (10.3mm x 38.1mm) Time-Delay, Class CC, Rejection Type

Construction: Melamine tube. Voltage Rating: 600 VAC. Interrupting Rating: 200,000A RMS Sym. Approvals: Std. 248-4, Class CC; UL Listed, Guide JDDZ, File E4273; CSA Certified, Class 1422-01, File 53787.



| Mfr.'s Type & Amp Rating | Each | Mfr.'s Type & Amp Rating | Each |
|--------------------------|-------|--------------------------|-------|
| FNQ-R-1/4 | 14.10 | FNQ-R-2-1/2 | 14.10 |
| FNQ-R-4/10 | 15.60 | FNQ-R-3 | 12.54 |
| FNQ-R-1/2 | 12.54 | FNQ-R-4 | 13.54 |
| FNQ-R-6/10 | 15.60 | FNQ-R-5 | 12.66 |
| FNQ-R-8/10 | 13.88 | FNQ-R-6 | 14.10 |
| FNQ-R-1 | 12.38 | FNQ-R-7-1/2 | 14.90 |
| FNQ-R-1-1/2 | 12.66 | FNQ-R-8 | 14.10 |
| FNQ-R-2 | 12.66 | FNQ-R-10 | 13.54 |



CBC is a full line BUSSMANN distributor. Consult us for complete information on products not shown in this catalog.