

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Type

FP3011248BLACK Thin-Wall Heat Shrink Tubing, 1/2 - 48", BK *Minnesota Mining (3M)*

3M 7000133508 3M™ Heat Shrink Thin-
Tubing That Provides A Balance Of Electrical, Physical and Chemical Properties, Making It Ideal For Industrial and Military Applications. This Tubing Has A 2:1 Shrink Ratio and Provides Flame Retardant Insulation For 600V Rated Applications. It Has A Flexible Polyolefin Construction That Offers Moisture Seal Protection. 0.1300 (lbs/each) Splicing & Terminating Kits THIN-WALL HEAT SHRINK TUBING, 1/2 - 48", BK 3M 7000133508 3M™ Heat Shrink Thin- 3M™ Heat Shrink Tubing FP-301 is color coded for quick and east
Splicing & Terminating Kits THIN-WALL HEAT SHRINK TUBING, 1/2 - 48", BK 3M 7000133508 3M™ Heat Shrink Thin- 3M™ Heat Shrink Tubing FP-301 is color coded for quick and easy
THIN-WALL HEAT SHRINK TUBING, 1/2 - 48", BK 3M 7000133508 3M™ Heat Shrink Thin- 3M™ Heat Shrink Tubing FP-301 is color coded for quick and easy
3M 7000133508 3M™ Heat Shrink Thin- 3M™ Heat Shrink Tubing FP-301 is color coded for quick and easy
3M™ Heat Shrink Tubing FP-301 is color coded for quick and easy
3M™ Heat Shrink Tubing FP-301 is color coded for quick and easy
tubing is used as shrink fit, electrical insulation over cable splices or terminations. The high expansion ratio tubing is mechanically tough, easily markable and resists cold flow. It is ideal for lightweight wire harness covering, fire resistant covering, wire marking, wire bundling and component packaging. It withstands temperatures of 67 to 275 degrees F (55 to 135 degrees
3M™ Heat Shrink Tubing FP-301 is a general purpose, thin wall tubing that provides a balance of electrical, physical and chemical properties, making it ideal for industrial and military applications. This tubing has a 2:1 shrink ratio and provides flame retardant insulation for 600V rated applications. It has a flexible polyolefin construction that offers moisture seal protection.
3M™ Heat Shrink Thin-Wall Flexible Polyolefin Tubing FP-301
Flexible, Polyolefin
3M
00051128595916
7000133508
051128595916

Single (Thin) Wall



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Availability Status	Inactive
Packaging Carton	1
Package	12
Weight Per each	0.13
Uses, Certifications, and Standards standard	UL, CSA, ABS