

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



UPC

FSD212 2G FSD-Box Crouse-Hinds

Catalog Number	FSD212
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet FS Device Box, Shallow, Feraloy Iron Alloy, Two-Gang, D Shape, 3/4"
Weight per unit	
Product Category	
0, 3	
eatures	(2) One End, (1) Other End
Cable Entry dimensions	4.6300 IN X 1.6900 IN X 6.0600 IN
Material	Electrogalvanized With Aluminum Acrylic Painted Feraloy Iron Alloy
imensions and Weight	
Size	3/4 in
escriptions	
	2G FSD-BOX
Description extra long description	
Features	Crouse-Hinds series FS and FD device boxes are installed in non-hazardous area conduit systems to accommodate wiring devices, act as pull boxes or provide openings for taps and splices. They are suitable for use in wet locations when used with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, hub configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable iron boxes are also a
Long Description	Eaton Crouse-Hinds series Condulet FS device box, Shallow, Feraloy iron alloy, Two-gang, D shape, 3/4"
Product Type	3/4 NPT Iron FS BX Two GNG MTG Lugs
Special Features	Configuration Type FSD, With Mounting Lug, Dimension 4-5/8 In Width X 1-7/8 In Depth X 6-1/16 In Height
lanufacturer Information	
Brand	Eaton
GTIN	00782274415208
Manufacturers Part Number	FSD212

782274415208



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	ΗΔ7ΔΡΩΟΙΙς Ι ΟΛΔΤΙΟΝ ΕΙΤΤΙΝΙΟς
Туре	DEVICE BOX
Packaging	
Carton	1
Weight Per each	3.6
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	SURFACE
standard	UL 514, CSA C22.2, Federal Specification W-C-5860