



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



G1.5X2LG6 LT. Grey Wiring Duct *Panduit Corporation*

| | |
|------------------|--|
| Catalog Number | G1.5X2LG6 |
| Manufacturer | Panduit Corporation |
| Description | The G1.5X2LG6 Panduct Lead-Free PVC Wide Slot Wiring Duct Feature A Wide Slot/Finger Design That Provides Greater Sidewall Rigidity and Is Suitable With A Range Of Wire Bundle Sizes. UL 94 Flame Class Of V-0 With A UL Recognized Continuous-Use Temperature Up to 122°F (50°C). Mounting Holes Provided. 1.5" X 2.0" (38.1 MM X 50.8 MM) and 6' (1.8 M) Long. Cover Sold Separately. Color Light Gray. |
| Weight per unit | 2.0 (lbs/each) |
| Product Category | Ducts, Raceways, Runways, Tray |

Features

| | |
|------------|----------------|
| connection | Mounting Holes |
| Material | PVC |
| media | Yes |

Material, Color, and Finish

| | |
|-------|------------|
| Color | Light Gray |
|-------|------------|

Dimensions and Weight

| | |
|--------|-------------|
| Length | 6.00 |
| Size | 1.75 x 2.12 |
| Width | 1.75 |

Descriptions

| | |
|------------------------|--|
| Description | LT. GREY WIRING DUCT |
| extra long description | PAN G1.5X2LG6 Panduct® G1.5X2LG6 Ba |
| Long Description | The G1.5X2LG6 Panduct Lead-Free PVC Wide Slot Wiring Duct feature a wide slot/finger design that provides greater sidewall rigidity and is suitable with a range of wire bundle sizes. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Mounting holes provided. 1.5" x 2.0" (38.1 mm x 50.8 mm) and 6' (1.8 m) long. Cover sold separately. Color Light Gray. |
| Product Type | Panduct® G1.5X2LG6 Base Wiring Duct |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | PANDUIT |
| GTIN | 00074983545797 |
| Manufacturers Part Number | G1.5X2LG6 |
| UPC | 074983545797 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description WIRE DUCT AND COVERS

Type Base Wiring Duct

Availability

minimum qty 6

Packaging

Carton 6

Package 120

Weight Per each 2

Uses, Certifications, and Standards

Application Wide slot/finger design provides greater sidewall rigidity and can
be used in a wide range of applications

standard RoHS Compliant, UL Recognized, CE Compliant; CSA Approved