



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



GC2626 4-2/0 1-Bolt Ground Conn *Burndy LLC*

| | |
|------------------|--|
| Catalog Number | GC2626 |
| Manufacturer | Burndy LLC |
| Description | Mechanical Grounding Connector, 2 Cables to 1/4" Thick Bar, 4 Awg (Sol)-2/0 Awg (STR). |
| Weight per unit | 0.2500 (lbs/each) |
| Product Category | Large Terminals & Connectors |

Features

| | |
|----------|--------|
| Material | Copper |
|----------|--------|

Descriptions

| | |
|------------------------|---|
| Description | 4-2/0 1-BOLT GROUND CONN |
| extra long description | BUR GC2626 4-2/0 CU-BAR (2)2PC GRD |
| Long Description | Mechanical Grounding Connector, 2 Cables to 1/4" Thick Bar, 4 AWG (Sol)-2/0 AWG (Str). |
| Product Type | Mechanical |
| Special Features | Features: High Copper Alloy Ground Connector For Joining A Wide Range Of Two Parallel Cables To 1/4 IN Thick Bar, Type GC Separates Cable From Bar, GCM Clamps Cable To Bar Surface, One-Wrench Installation, UL467 Listed, The High Copper Alloy Cast Body And DURIMUM Bolts, Nuts, And Lockwashers Make The GC And GCM Suitable For Direct Burial In Concrete Or Ground, Width: 1-3/4 IN, Installation Torque: 240 IN-LB, Bar Thickness: 1/4 IN, Height: 2 IN |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | BURNDY |
| GTIN | 00781810231661 |
| Manufacturers Part Number | GC2626 |
| UPC | 781810231661 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|--|
| Category Description | SERVICE ENTRANCE FITTINGS: Weatherheads & Grounding Fittings & Ground Rods |
| Type | GC |

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Package | 12 |
| Weight Per each | 0.25 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

For Joining A Wide Range Of Two Parallel Copper Cables, Direct
Burial In Concrete Or Ground

standard

UL467