



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



GDB5A 5A 250V Fa Low-Break IEC Glass Fuse *Bussmann Fuses*

| | |
|------------------|---|
| Catalog Number | GDB5A |
| Manufacturer | Bussmann Fuses |
| Description | Fuse, Fast Acting Fuse Speed, Ferrule End X Ferrule End Connection, 5 A, 250 V Ac, Glass (Tube);Brass (End Cap) Material, Ferrule Terminal, 5.2 MM Diameter, 20 MM Overall Length |
| Weight per unit | 0.0050 (lbs/each) |
| Product Category | Small Dimension Fuses |

Features

| | |
|-----------------|---------------------------|
| amperage rating | 5 A |
| connection | Ferrule End X Ferrule End |
| dimensions | X X 0.7874 IN |

Dimensions and Weight

| | |
|------|------------------------------------|
| Size | 5.20 mm Diameter X 20.00 mm Height |
|------|------------------------------------|

Descriptions

| | |
|------------------------|---|
| Description | 5A 250V FA LOW-BREAK IEC GLASS FUSE |
| extra long description | BUSS GDB-5A BUSS SMALL DIMENSION FU |
| Features | Fast-acting, low breaking capacity 5 mm x 20 mm ferrule fuse designed to IEC 60127-2 for overcurrent protection of electronic circuits. Install into a Bussmann Series fuse holder, block, or fuse clip, or purchase with available axial leads for thru-hole installation Eaton's GDB fast-acting, low breaking capacity 5mm x 20mm ferrule fuses are designed to IEC 60127-2 for overcurrent protection of electronic circuits. Order in cartridge fuse format and install into a Bussmann Series fuse holder, block, or fuse |
| Special Features | Low Breaking Capacity, Interrupt Rating 50 Amp at 250 V, Material Glass Tube, Nickel Plated Brass Endcap |

Manufacturer Information

| | |
|-------|-----------------------|
| Brand | Eaton Bussmann series |
| GTIN | 00051712431835 |
| UPC | 051712431835 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|---------------------------|
| Category Description | GLASS FUSES (and ceramic) |
| Type | Fast-Acting Fuse |

Packaging

| | |
|-----------------|-------|
| Carton | 1 |
| Package | 5 |
| Weight Per each | 0.005 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

| | |
|------------------|---|
| Frequency Rating | 50 |
| standard | VDE,RoHS Compliant,CE Marked,CCC Marked |