

## **ELLIOTT ELECTRIC SUPPLY**

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685 We Deliver...Lower Cost, Quality Products, & Personal Service



## GFTWRST20LA 20A Comm Self Test TRWR GFR LT Almond Hubbell Wiring Devices

Catalog Number	GFTWRST20LA
Manufacturer	Hubbell Wiring Devices
Description	Power Protection Devices, Receptacle, Self Test, Gfci, TRWR, Commercial Grade, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Light Almond
Weight per unit	0
Product Category	
eatures	
amperage rating	20
connection	Terminal Screws
Number of Wires	
pallet quantity	-
Phase	1
Poles	2-Pole
Voltage Rating	125
Wattage	
Wire Size	#14 to #12
imensions and Weight	
Size	Standard Sized Product
escriptions	
Description	20A COMM SELF TEST TRWR GFR LT ALMOND
extra long description	HWDK GFTWRST20LA 20A COMM SELF TEST
Features	AUTOGUARD <sup>®</sup> Self Test Technology 1st introduced by Hubbell
	over 10 years agoself test monitoring now required in 2015 U 943 GFCI Safety Standard Hubbell AUTOGUARD® GFCI receptacles continually test and monitor for "people protection capability" automatically. This patented safety feature includes disconnecting power to the receptacle if critical components ar damaged and GFCI protection is lost. GFCI auto-monitoring is conducted continuously within every 30 seconds. Also, clear visual indicators are pro
Long Description	Power Protection Devices, Receptacle, Self Test, GFCI, TRWR, Commercial Grade, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Light Almond
Product Type	20A Comm Solf Tost TD\M/D CED   T Almond
Special Features	Self Test, Tamper and Weather Resistant



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Manufacturer Information**

Brand	WIRING DEVICE-KELLEMS
GTIN	00883778122699
Manufacturers Part Number	GFTWRST20LA
series	Heavy Duty
UPC	883778122699
Taxonomies, Classifications, and C	ategories
	Commercial GFCI devices
Туре	Tamper-Resistant, Weather Resistant
Availability	
Status	Inactive
Packaging	
Carton	
Package	10
Weight Per each	0.35
Uses, Certifications, and Standard	S
Application	Commercial Grade
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Screw Mount
nema rating	5-20R
standard	Meets All NEC <sup>®</sup> Requirements