

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### **GL3038 3/0 1-Hole Compression Lug 3/8" Bolt** *Nsi Industries*

| เพิ่ม แนนวินาธิว              |   |
|-------------------------------|---|
| Catalog Number                | GL3038  |
| Manufacturer                  | Nsi Industries  |
| Description                   | 1 Hole Short Barrel Copper Compression Lug W/ Peep Hole 3/0 Awg - 3/8" Bolt Short Barrel Copper Compression Lugs With Peep Hole Is A Type Of Copper Compression Connector That Is Produced From High Conductivity Copper Tubing. They Are Tin-Plated to Provide Corrosion Resistance and Are Marked With Die Index and Color Coded For Easy Reference. Listed For 35KV Maximum When Properly Installed. |
| Weight per unit               | 0.0800 (lbs/each)   |
| Product Category              | Large Terminals & Connectors  |
| Features                      |   |
| Cable Size                    | 3/0 AWG (STR)   |
| Material                      | Copper  |
| Number of Holes               | 1   |
| Stud Size                     | 3/8   |
| Voltage Rating                | 600 V   |
| Warranty                      | 1 YEAR  |
| Material, Color, and Finish   |   |
| Color                         | Orange  |
| Finish                        | Tin Plated  |
| Dimensions and Weight<br>Size | L=2.36 - W=.900 - OD=.620 - ID=.490   |
|                               |   |



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| _            |    |    | •  |   |                     |   |
|--------------|----|----|----|---|---------------------|---|
| De           | ~~ | ~r | ın |   | $\boldsymbol{\sim}$ | n |
|              |    |    |    |   |                     |   |
| $\mathbf{r}$ | ~~ | •  |    | • | v                   |   |
|              |    |    | •  |   |                     |   |

| Description             | 3/0 1-HOLE COMPRESSION LUG 3/8" BOLT  |
|-------------------------|---|
| extra long description  | NSI GL3038 CU CMP Lug Short 3/0 AWG   |
| Features                | 1 Hole Short Barrel Copper Compression Lug w/ Peep Hole 3/0 AWG - 3/8" Bolt Short Barrel Copper Compression Lugs with Peep Hole is a type of copper compression connector that is produced from high conductivity copper tubing. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed. |
| Long Description        | 1 Hole Short Barrel Copper Compression Lug w/ Peep Hole 3/0 AWG - 3/8" Bolt Short Barrel Copper Compression Lugs with Peep Hole is a type of copper compression connector that is produced from high conductivity copper tubing. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed. |
| Product Type            | Cu CMP Lug Short 3/0 Awg 3/8 Bolt Size  |
| Special Features        | 3/0 AWG (STR) - 3/8 Mounting Hole   |
| anufacturor Information |   |

#### **Manufacturer Information**

| Brand                     | NSi            |  |
|---------------------------|----------------|--|
| GTIN                      | 00662381036117 |  |
| Manufacturers Part Number | GL3038         |  |
| UPC                       | 662381036117   |  |

#### **Taxonomies, Classifications, and Categories**

| Category Description | Comp & Mech Lugs and Butt Splices |
|----------------------|-----------------------------------|
| Туре                 | Short Barrel - One Hole           |

#### **Packaging**

| Carton          | 1    |  |
|-----------------|------|--|
| Package         | 25   |  |
| Weight Per each | 0.08 |  |

#### Uses, Certifications, and Standards

| Application              | Terminate, Splice, Tap Power Connectors |
|--------------------------|---|
| environmental conditions | 90 C                                    |
| Mounting                 | 3/8 Mounting Hole                       |
| standard                 | UL486A/B, UL467 (8 AWG -3/0 AWG)        |