



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



H200X165H1T TT, Heat Shrink, 2"X1.65", 1 Panduit Corporation

Catalog Number	H200X165H1T
Manufacturer	Panduit Corporation
Description	The H200X165H1T Military-Grade Polyolefin Heat-Shrink Label Is A Single-Sided Printable. It Offers Crisp, Clear Legends With Superior Readability For Quick and Easy Label Production. The Heat-Shrink Sleeve Is Designed to Provide A Clear, Reliable, and Durable Way to Identify Wires and Cables. Designed For Use With Panduit TDP Printers. Shrink Ratio 3:1. 2" X 1.65" (50.8 MM X 41.9 MM). Color White. 250 Labels Per Roll.
Weight per unit	2.3 (lbs/each)
Product Category	Markers & Marking Tapes

Features

labels per package	250
Material	Polyolefin
Printer Type	THERMAL TRANSFER
Temperature Range	275

Material, Color, and Finish

Color	White
-------	-------

Dimensions and Weight

Length	NA
Size	2.00 x 1.65
Width	2

Descriptions

Description	TT,HEAT SHRINK,2"X1.65",1
extra long description	PAN H200X165H1T H200X165H1T Heatshr
Long Description	The H200X165H1T Military-Grade Polyolefin Heat-Shrink Label is a single-sided printable. It offers crisp, clear legends with superior readability for quick and easy label production. The heat-shrink sleeve is designed to provide a clear, reliable, and durable way to identify wires and cables. Designed for use with Panduit TDP printers. Shrink ratio 3:1. 2" x 1.65" (50.8 mm x 41.9 mm). Color White. 250 labels per roll.
Product Type	H200X165H1T Heatshrink, Po, White, Mil Grade, 250 LBLs, TT,

Manufacturer Information

Brand	PANDUIT
GTIN	00074983526772
Manufacturers Part Number	H200X165H1T
UPC	074983526772



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
Type	Heat Shrink Label

Packaging

Carton	1
Weight Per each	2.3499

Uses, Certifications, and Standards

standard	Meets UL Standard 224 for flammability and AMS-DTL-23053/5C (Class 1 and Class 3). Meets SAE-AS81531, MIL-STD-883F Method 2015.13, Solutions A, B, and D, and D202F, and MIL-STD-202G Method 215K, Solutions A, C, and D when printed with resin or hybrid therm
----------	--