

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



HBL4710ST LKG SGL RCPT, 15A 125V, L5-15R, BK, ST Hubbell Wiring Devices

0		
Catalog Number	HBL4710ST	
Manufacturer	Hubbell Wiring Devices	
Description	Locking Devices, Edgeconnect™ Twist-Lock®, Industrial, Flush Receptacle, 15A 125V, 2-Pole 3-Wire Grounding, L5-15R, Screwless Terminal, Black	
Weight per unit	0.1500 (lbs/each)	
Product Category	Wiring Devices	
atures		
connection	EdgeConnect™ Screwless Termination	
Dielectric Strength	-	
Material	Nylon	
Number of Wires	3	
Phase	1	
Poles	2	
Voltage Rating	15 VAC	
mensions and Weight		
Size	Standard Sized Product	
escriptions		
Description	LKG SGL RCPT, 15A 125V, L5-15R, BK, ST	
extra long description	HWDK HBL4710ST LKG SGL RCPT, 15A 12	
Features	EdgeConnect™ Screwless Termination system, simply insert the wire and press the plunger down. No tools are required. That connection is fool-proof and long lasting, to all but guarantee a high quality result. Any qualified installer regardless of level of training can guarantee a high quality result.	
Long Description	Locking Devices, EdgeConnect™ Twist-Lock®, Industrial, Flush Receptacle, 15A 125V, 2-Pole 3-Wire Grounding, L5-15R, Screwless Terminal, Black	
Product Type	LKG SGL RCPT, 15A 125V, L5-15R, BK, ST	
Special Features	EdgeConnect™ Technology, Screwless Termination	
anufacturer Information		
Brand	WIRING DEVICE-KELLEMS	
GTIN	00783585719634	
Manufacturers Part Number	HBL4710ST	
series	EdgeConnect™	
UPC	783585719634	



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, C	classifications, and	Categories
---------------	----------------------	------------

Category Description	Residential Switches
Туре	RECEPTACLE
Packaging	
Carton	1
Package	10
Weight Per each	0.15
Uses, Certifications, and Standards	
Application	Industrial
onvironmental conditions	ID20 Cuitability

Use

Application	Industrial
environmental conditions	IP20 Suitability
Mounting	Screw Mount
nema rating	L5-15R
standard	Certified to CSA C22.2 No.42; Fed. Spec. W-C-596; Listed to UL 498