



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## HSTT0948Q Heat Shrink Thin, .09"(2.4MM) Dia, Black Panduit Corporation

Catalog Number	HSTT0948Q
Manufacturer	Panduit Corporation
Description	The HSTT09-48-Q Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1. Temperature Range: -67°F to 275°F (-55°C to 135°C). Flame Retardant, Cross-Linked Polyolefin. 0.093" Diameter X 4' Long (2.4 MM X 1.2 M). Color Black. 25 Per Package.
Weight per unit	0.0292 (lbs/each)
Product Category	Insulating Materials

### Features

continuous operating temperature	275
flammability	Flame Retardant
Inside Diameter	0.046
media	Yes
outside diameter	0.093
Shrink Ratio	2:1

### Material, Color, and Finish

Color	Black
-------	-------

### Dimensions and Weight

Thickness	0.02
-----------	------

### Descriptions

Description	HEAT SHRINK THIN, .09"(2.4MM) DIA, BLACK
extra long description	PAN HSTT09-48-Q Dry-Shrink™ HSTT09-
Long Description	The HSTT09-48-Q Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Flame retardant, cross-linked polyolefin. 0.093" Diameter x 4' Long (2.4 mm x 1.2 m). Color Black. 25 per package.
Product Type	Dry-Shrink™ HSTT09-48-Q Heatshrink, Black, Po, 4' L, 0.093"

### Manufacturer Information

Brand	Panduit®
GTIN	00074983905881
Manufacturers Part Number	HSTT09-48-Q
UPC	074983905881



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description ..... HEAT/COLD SHRINK  
Type ..... Heat-Shrink Tubing

## Packaging

Carton ..... 25  
Weight Per each ..... 0.0292

## Uses, Certifications, and Standards

Application ..... For Dry Locations;Insulating and protecting wires and cables  
standard ..... Mil Spec: AMS-DTL-23053/5 Class 1;UL: E122770