

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **HSTT1248Q Heatshrink Tubing BLK 1/8** *Panduit Corporation*

Catalan Niverslage	LICTT1240O
Catalog Number  Manufacturer	HSTT1248Q
Description	Panduit Corporation Panduit Thin-Wall Heat Shrink Tubing Shrinks Around Wires,
Description	Connectors, Joints and Terminals When Heated to Protect
	Against Abrasion, Fire and Chemicals. Cross-Link Polyolefin,
	0.12"D X 3.94'L (3.2MM X 1.2M), Black, 25PC.
Weight per unit	0.7600 (lbs/each)
Product Category	Insulating Materials
Features	
flammability	Flame Retardant
media	Yes
outside diameter	0.125
Shrink Ratio	2:1
Material, Color, and Finish	
Color	Black
Dimensions and Weight Thickness	0.02
	0.02
Descriptions	LIFATOLIDIA IX TUDINIO DU VA 4/0
Description	HEATSHRINK TUBING BLK 1/8
extra long description	PAN HSTT12-48-Q Dry-Shrink HSTT12-4
Long Description	Panduit Thin-wall Heat Shrink Tubing shrinks around wires,
	connectors, joints and terminals when heated to protect against
	abrasion, fire and chemicals. Cross-link Polyolefin, 0.12"D x 3.94' (3.2mm x 1.2m), Black, 25pc.
Product Type	Dry-Shrink HSTT12-48-Q Heatshrink, Black, Po, 0.125" to 0.06
<b>3.</b>	Dry 311111K 1131112 40 Q 11cat311111K, Dlack, 1 0, 0.123 to 0.00
Manufacturer Information	DANIDI IIT
Brand	PANDUIT 00074983905898
GTIN  Manufacturers Part Number	
UPC	HSTT12-48-Q 074983905898
Taxonomies, Classifications, and	
Category Description	HEAT/COLD SHRINK
Packaging	
Carton	25
Weight Per each	0.76

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Uses, Certifications, and Standards**

Application	For Dry Locations
standard	UL Recognized