



HSTT150485C HSTT150485C HT Shrink Tub *Panduit Corporation*

Catalog Number

HSTT150485C

Manufacturer

Panduit Corporation

Description

The HSTT150-48-5C Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1.

Temperature Range: -67°F to 275°F (-55°C to 135°C).

Cross-Linked Polyolefin. 1.50" Diameter X 4' Long (38.1 MM X 1.2 M). Color Clear. 5 Per Package.

Weight per unit

1.0 (lbs/each)

Product Category

Insulating Materials

Features

media

Yes

Descriptions

Description

HSTT150485C HT SHRINK TUB

extra long description

PAN HSTT150-48-5C Dry-Shrink™ HSTT1

Long Description

The HSTT150-48-5C Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1.

Temperature range: -67°F to 275°F (-55°C to 135°C). Cross-linked polyolefin. 1.50" Diameter x 4' Long (38.1 mm x 1.2 m). Color Clear. 5 per package.

Product Type

Dry-Shrink™ HSTT150-48-5C Heatshrink, Clear, Po, 4'L, 1.5"

Manufacturer Information

Brand

PANDUIT

GTIN

00074983906673

Manufacturers Part Number

HSTT150-48-5C

UPC

074983906673

Taxonomies, Classifications, and Categories

Category Description

HEAT/COLD SHRINK

Packaging

Carton

50

Package

5

Weight Per each

1